Drwak 3410

Benefits

- Savings on your waste collection
- Tidy premises
- Space saving
- Compliance to meet your legal obligations

Features

- Front loading
- Operator friendly
- Large loading aperture
- 24 ton pressure
- Quiet operation
- Fast cycle time
- Secure door locking





Technical specifications

Dimensions

3410 A: 2994 (2794^I) mm 1590 mm B: 1103 mm C D: 2270 mm 1107 mm F: F:* 2150 mm *Transport Height ^I Option





Loading aperture		
Width:	1200 mm	
Height:	554 mm	
<u> </u>	55111111	
Cycle time		
	35 secs	
Press force		
	24 ton, 240 kN	
Bale size		
Width:	1200 mm	
Depth:	800 mm	
	1000 mm	
Height:	1000 mm	
Bale weight		
Cardboard:	Up to 300 kg	
Plastic:	Up to 450 kg	
Chamber dimension		
(internal)		
Width:	1200 mm	
Depth:	800 mm	
	1560 mm	
Height:		
Weight (machine		
Total:	1440 kg	
Noise level		
	59.5 db (A)	
Protection class		
i i otection class	IP 55	
a .		
Operating power	·	
	011	

3-phase 3x400 V, 50 Hz **Electrical connection**

CEE plug/16 A, 10 A fuse Operating voltage Via transformer 24 V AC/DC Paint Two-part paint and powder coat

with phosphatising as base Oil volume/type

20,8 | ISO VG 32-68 SAE 10

from +5 °C and warmer Hydraulical data 235 har Working pressure

vvorking pressure:	ZSS Dar
Relief pressure:	250 bar
Press force:	24 ton, 240 kN
Piston stroke:	1000/800 ¹ mm
Press force per cm ²	: 2,5 kg

AB Orwak

Box 58, SE-576 22 Sävsjö, Sweden Tel: +46 382-157 00, Fax: +46 382-106 07 E-mail: info@orwak.se

Simple baling of big volumes

Orwak 3410 offers high capacity and simple handling to the highest operator safety. It is suitable for customers such as large industries and supermarkets with big amounts of packaging materials.

Generous loading aperture

- operator friendly.

Silent operation contributes to a better working environment

Due to a new type of hydraulics, Orwak has introduced "the silent family" - a line of balers with low sound emission. A silent operating machine contributes to improving the working environment for the employees. Orwak 3410 has a noise level of only 59.5 dB!

Switch between LP and HP

Compacting cardboard or plastic foil? A switch conveniently located on the side of the machine makes it simple to alter the setting from High Pressure for cardboard to Low Pressure for plastic foil.

Our promise to You!

- · Orwak financial solutions
- · Orwak non-stop service

For further information please contact Your local Orwak dealer.

The Orwak 3410 takes care of most of your waste

Plastic foil Shrink film Plastic bags

OK

Metal Cans Aluminium cans Food cans

Paint cans Other metals Steel straps

Paper

Cardboard

Shredded

Paper sacks

Plastic containers PET bottles Jugs/bottles

> Other plastics Plastic straps

Semi-dry Waste Bagged general waste Wet

Juice boxes, . Tetra paks

Special Steel drums Hazardous waste

Perfect choice

Other materials contact us

For more info. contact us or visit our website www.orwak.com We reserve the right to make changes to specifications without prior notice. Bale/bag/bin weights are dependent upon material type.





