## **Butane Mini Soldering Iron with Piezo Ignition**

- Piezo electronic ignition system for reliable ignition every time
- · Adjustable gas flow valve controls temperature range
- Tip temperature 750° F / 900° F
- Up to 30 minutes continuous use on medium setting
- Refillable with Weller WB1 or WB2 filtered butane
- · Also operates as a mini-torch when the tip is removed
- Window allows you to see fuel level
- · Base allows tool to stand for hands free operation
- Safety cap can be replaced on tool for secure storage
- Use for soldering, heat shrink tubing, electrical, and electronics

See page 239 for soldering tip listing.



Cat	UPC			Pack Wt.		Shelf
No.	No.	Description	Packed	lb	kg	Pack
ML500MP	037103220912	Butane Mini Soldering Iron with Piezo Ignition	Clamshell	0.62	0.28	4

## **Replacement Soldering Tips for ML500MP Iron**

- ML501: 0.06" (1.6 mm) conical replacement tip
- ML502: 0.09" (2.4 mm) conical replacement tip
- ML503: Use for cutting rope, foam, wax, stencils, etc.









ML501

ML502

ML503

Cat	UPC	Pack Wt.			Shelf	
No.	No.	Description	Packed	lb	kg	Pack
ML501	037103220929	Conical Replacement Soldering Tip for ML500MP	Card	0.18	0.08	6
ML502	037103220936	Chisel Style Replacement Soldering Tip for ML500MP	Card	0.18	0.08	6
ML503	037103220905	Knife Style Replacement Soldering Tip for ML500MP	Card	0.18	0.08	6