



Orwak 3410 Sliding door

Benefits

- Savings on your waste collection
- Tidy premises
- Space and time saving
- Compliance to meet your legal obligations

Features

- Front loading
- Large loading aperture
- Sliding door
- Equipped with autostart
- Operator friendly
- Quiet operation
- Fast cycle time
- Secure door locking





Technical specifications

Dimensions

3410 Sliding door

- A: 2962 mm
- B: 1613 mm
- C: 1151 mm
- D: 2400 mm
- E: 1106 mm
- F: 2150 mm

*Transport Height



Loading aperture

Width: 1113 mm
Height: 550 mm

Cycle time

35 secs

Press force

(cardboard) 24 ton, 240 kN

Bale size

Width: 1200 mm
Depth: 800 mm
Height: 1000 mm

Bale weight

Cardboard: Up to 300 kg
Plastic: Up to 450 kg

Chamber dimension (internal)

Width: 1200 mm
Depth: 800 mm
Height: 1555 mm

Weight (machine)

Total: 1350 kg

Noise level

62.7 db (A)

Protection class

IP 55

Operating power

3-phase 3x400 V, 50 Hz

Electrical connection

CEE plug/16 A, 10 A fuse

Operating voltage

Via transformer 24 V AC/DC

Paint

Two-part paint and powder coat with phosphatising as base

Oil volume/type

20,8 l ISO VG 32-68 SAE 10 from +5 °C and warmer

Hydraulical data

Working pressure: 235 bar
Relief pressure: 250 bar
Press force: 24 ton, 240 kN
Piston stroke: 1000/800¹ mm
Press force per cm²: 2,5 kg

3410 Sliding door for easier and faster handling

For even easier and faster loading this model of 3410 has a sliding door that opens automatically after each cycle. 3410 Sliding door is also equipped with an autostart function which allows the baler to start compacting the material as soon as the door closes.

Safe and silent

3410 Sliding door is operator friendly and safe to use. Due to a new type of hydraulics the operation is silent (only 62.7 dB).

High capacity

3410 Sliding door has a generous loading aperture and offers high capacity. It is suitable for customers such as large industries and supermarkets with big amounts of packaging materials.

Switch between LP and HP

Compacting cardboard or plastic foil? A switch conveniently located on the side of the machine makes it simple to alter the setting from High Pressure for cardboard to Low Pressure for plastic foil.



Our promise to You!

- Orwak financial solutions
- Orwak money back guarantee
- Orwak non-stop service

For further information please contact Your local Orwak dealer.

The Orwak 3410-SD takes care of most of your waste

Paper

- Cardboard
- Shredded
- Paper sacks

Metal Cans

- Aluminium cans
- Food cans
- Paint cans

Other metals

- Steel straps

Plastic foil

- Shrink film
- Plastic bags

Plastic containers

- PET bottles
- Jugs/bottles

Other plastics

- Plastic straps

Semi-dry Waste

- Bagged general waste

Wet

- Juice boxes,
- Tetra paks

Special

- *Steel drums
- Hazardous waste

● Perfect choice

● OK

* Optional insert available for combined baler and drum crusher

*For more info, contact us or visit our website www.orwak.com
We reserve the right to make changes to specifications without prior notice.
Bale/bag/bin weights are dependent upon material type.*

AB Orwak

Box 58, SE-576 22 Sävsjö, Sweden
Tel: +46 382-157 00, Fax: +46 382-106 07
E-mail: info@orwak.se



Making sure less is more

www.orwak.com