

Combination Tools

STREAMLINE
TECHNOLOGY

SC 350

The STREAMLINE^{Technology} Combi Tool SC 350 performs spreading and cutting functions with one rescue tool. Cutting force and blade opening are similar to modern cutters and spreading force is similar to a light-weight spreader.

Applications



- First response rescue operations
- Rescue operation in buildings
- Disaster management and building collapse
- Traffic accidents

Features & Benefits

- Cutting and spreading in one tool
- Pulling with the Hurst® chain set
- Low oil requirement – suitable for portable hydraulic power units (ex. P 600 OB)
- Strong materials provide durability and prevent blade breakage
- Intelligent star-grip control valve provides access from every angle
- Quick opening and closing times to save valuable time
- Optimum handling through precisely balanced design





Specifications		Useful Components	
NFPA Cutter Rating	A6/B7/C7/D7/E7	 <p>Blade Arm</p> <p>Weight 5 lbs. (2.3 kg)</p>  <p>Adjustable Handle</p>  <p>KSV 8 - Chain Set</p> <p>Weight 19.6 lbs. (8.9 kg)</p>	
Cutting force up to	85,430 lbs. (380 kN)		
Round steel material up to dia.*	1.2 in. (30 mm)		
Spreading force up to	25,400 lbs. (113 kN)		
Spreading distance	14.1 in. (360 mm)		
Pulling force up to	10,228 lbs. (45.5 kN)		
Pulling distance	15 in. (381 mm)		
Oil requirement	4 cu. in. (66 cm ³)		
Dimensions: l x w x h	30.3 x 7.8 x 6.4 in. (770 x 199 x 163 mm)		
Weight	30.6 lbs. (13.9 kg)		
* According to EN 13204			
Power Units			
P 600 OB, P 610 OG, P610 OD, P 620 Series, P 640 Series, P 640 TRIMO			

Combination Tools

STREAMLINE
TECHNOLOGY

SC 550

The STREAMLINE^{Technology} SC 550 provides spreading force up to 50,500 lbs. and cutting force over 120,000 lbs. The tool offers versatility and power for fast operations in any rescue scenario. The SC 550 is excellent for first response operations.

Applications

- Traffic accidents
- Rescue operation on modern cars with reinforced parts
- Disaster recovery and building collapse
- Rescue operations in buildings

Features & Benefits

- Cutting and spreading in one tool
- Pulling with the Hurst® chain set
- Low oil requirement – especially suitable for mobile hydraulic power units (ex. P 600 OB)
- Intelligent star-grip control valve provides access from every angle
- Strong materials provide durability and prevent blade breakage
- Quick opening and closing times to save valuable time
- Optimum handling through precision of design





Specifications

NFPA Cutter Rating	A7/B9/C7/D9/E9
Cutting force up to	120,300 lbs. (535 kN)
Round steel material up to dia.*	1.5 in. (37 mm)
Spreading force up to	50,500 lbs. (225 kN)
Spreading distance	16.9 in. (430 mm)
Pulling force up to	17,530 lbs. (78 kN)
Pulling distance	12.6 in. (320 mm)
Oil requirement	6.6 cu. in. (108 cm ³)
Dimensions: l x w x h	33.9 x 9.6 x 7.1 in. (860 x 245 x 180 mm)
Weight	44 lbs. (20 kg)

* According to EN 13204

For Use With Power Units:

P 600 OB, P 610 OG, P610 OD, P 620 Series, P 640 Series, P 640 TRIMO

Useful Components



Blade Arm

Weight 8.6 lbs. (3.9 kg)



KSV 11/80 - Chain Set

Weight 29.3 lbs. (13.3 kg)