Cleans approximately 0.5 to 1 acres/hr

700 SERIES | MODEL 800 | MODEL 4500XL | MODEL 4700XL | MODEL 950 | MODEL 3000 | MODEL 5000

PRINTABLE VERSION

The Cherrington 800 Beach Cleaner is designed to work with compact tractors and is perfect for cleaning smaller public or private beaches, or any where sand cleaning is needed on a smaller scale. Remove sticks, stones, animal droppings, glass – and leave a beautiful screened beach!

The 800 Beach Cleaner has a cleaning width of 3', and performs best when pulled by a four wheel drive ATV or a 15 to 35 HP four wheel drive tractor.

Dual gauge wheels assure accurate and consistent cleaning depths. The Model 800 Beachcleaner's maximum cleaning depth is 3". The 800 comes with 2 separate screens for different sifting needs - 1/2" and 3/4" are standard, 3/8" and 1" screens are offered for special screening needs.







Two options for collecting and dumping debris!

The debris hopper on the Model 800 Beachcleaner has a capacity of 6.5 cu. ft. and empties through a manual open clams shell style door neatly onto the ground. An optional bagger system includes two heavy duty removable poly bags for convenient emptying into a receptacle of your choice.

For more information, take a look at our brochures or video clips.







Model 800 Beachcleaner Specifications – Metric

2.64 m Length: Width: 1.32 m 1.32 m Height: Weight: 599 kg **Maximum Screening Width:** 0.91 m Cleaning Depth: Up to 8 cm **Grooming Width:** 1.27 m 0.18 m³ **Hopper Capacity: Hopper Dump Height: Ground Dump** Maximum Cleaning Speed: Up to 5 km/hr Requires Small Tractor **Tow Vehicle Requirements:** or tow vehicle. Onboard 6.5 hp Honda powers screen system.

Model 800 Beachcleaner Specifications – Standard

8 ft. 8 inches Length: 4 ft. 4 inches Width: Height: 4 ft. 4 inches Weight: 1320 lbs **Maximum Screening Width:** 3 ft. Up to 3 inches Cleaning Depth: **Grooming Width:** 4 ft. 2 inches 0.25 vd3 **Hopper Capacity: Hopper Dump Height: Ground Dump Maximum Cleaning Speed:** Up to 3 mph **Tow Vehicle Requirements:** Requires Small Tractor

or tow vehicle.

Onboard 6.5 hp Honda powers screen system.

Other Towing Requirements:

Flotation tires are recommended and hydrostatic drive preferred. Note that sand and soil surfaces vary, and all tow vehicles must have sufficient traction and flotation for the particular sand or application in which they operate.