



UNO® D.O.T. Safety cans are FM approved and D.O.T. compliant with an integrated fill-and-pour spout.




Usage Mode
Simply disengage the hold-down bracket when the can is not being used for transportation purposes. The hold-down bracket can be secured firmly to the top of the spout to prevent loss or damage.



Transport Mode
To prevent vapor release and spills during transport, a fusible link protected hold-down bracket is tethered to the spout and equipped with an easy-to-grasp tightening screw.



Easy Pouring
Nothing beats UNO® for usability! The exclusive spout is ergonomically designed for comfortable pouring. Self-venting spout releases liquid with accuracy for no-glug, spill free liquid transfers.



Accommodates oil additives for two cycle engines



Leading the Advancement of Safety

D.O.T. COMPLIANT AND FM APPROVED

Justrite's D.O.T. cans have earned approvals from both UN and FM, giving you two cans in one ... a transport can and a safety can! You will be in compliance in "over-the-road" conditions, and also maintain the protection of a traditional safety can to remain OSHA and NFPA compliant.

Compliance with Department of Transportation regulations for over-the-road transport of flammables is simpler and more affordable than ever with Justrite's **UNO® D.O.T. Compliant Safety Cans** – ideal when remote usage of gas fueled equipment is needed.

Because there is only one multi-task spout, changing from transport to usage mode is a snap! To prevent vapor release and spills during transport, a hold-down bracket is tethered to the spout and equipped with a big, easy-to-grasp tightening screw. When used for the transport of fuel, the dual fusible link bracket is easy to engage and guards against content spillage and vapor release as required by D.O.T. The fusible link melts at 165°F (74°C) to prevent dangerous pressure build-up at elevated temperatures. Simply disengage the fusible link bracket when the can is not being used for transportation purposes and the can acts like a normal safety can. UNO's exclusive Safe-Squeeze® trigger mechanism opens the piston actuated spout and vacuum release valve for accurate pouring. A release of the handle instantly closes the valve to guard against spills.

Along with the economically-priced UNO® D.O.T. version, the **Original Justrite D.O.T. Safety Can** is also available. Both have built-in safety features that include internal flame arresters to dissipate heat and prevent flashback ignition; leaktight, self-closing lid; automatic venting between 3 and 5 psig (0.2 and 0.35 bar); and heavy roll bars to protect the spout.

Meets D.O.T. and HM-181 requirements. United Nations Approved... UN Marking: 1A1/Y1.2/100. Accepted container under CARB.

Type II Transport and Dispensing Safety Cans

Description and Capacity	Hose Dimensions		Can Dimensions		Approval/Lstg. Regulation*	UNO® Red Model No.	UNO® Yellow Model No.	Original Red Model No.	Can Dimen. Outer Dia. x H
	Outer Dia. x L (mm)	Outer Dia. x H (mm)	Outer Dia. x L (mm)	Outer Dia. x H (mm)					
1 gallon (4L) D.O.T. Type II Can	5/8" x 9"(16 x 229)	10 1/4" x 11 5/8"(260 x 295)	10 1/4" x 11 5/8"(260 x 295)	10 1/4" x 11 5/8"(260 x 295)	FM,D.O.T.,UN	10361	10361Y	-	-
2 1/2 gallon (9L) D.O.T. Type II Can	5/8" x 9"(16 x 229)	10 1/4" x 16 1/2"(260 x 419)	10 1/4" x 16 1/2"(260 x 419)	10 1/4" x 16 1/2"(260 x 419)	FM,D.O.T.,UN	10661	10661Y	10541	11 1/2" x 13 1/2"(292 x 343)
2 1/2 gallon (9L) D.O.T. Type II Can	1" x 9"(25 x 229)	10 1/4" x 16 1/2"(260 x 419)	10 1/4" x 16 1/2"(260 x 419)	10 1/4" x 16 1/2"(260 x 419)	FM,D.O.T.,UN	10660	10660Y	10540	11 1/2" x 13 1/2"(292 x 343)
5 gallon (19L) D.O.T. Type II Can	5/8" x 9"(16 x 229)	12 5/8" x 18 1/4"(321 x 464)	12 5/8" x 18 1/4"(321 x 464)	12 5/8" x 18 1/4"(321 x 464)	FM,D.O.T.,UN	10861	10861Y	10841	11 1/2" x 18"(292 x 457)
5 gallon (19L) D.O.T. Type II Can	1" x 9"(25 x 229)	12 5/8" x 18 1/4"(321 x 464)	12 5/8" x 18 1/4"(321 x 464)	12 5/8" x 18 1/4"(321 x 464)	FM,D.O.T.,UN	10860	10860Y	10840	11 1/2" x 18"(292 x 457)

*See page 8 for Regulation Key.

