Customize and protect workstations.

Environmente Low-profile Gator® Accumulation Centers are the economical solution to spill concerns during drum filling and dispensing operations. They are ideal for chemical or battery storage needs. "Gator-Tuff" seamless construction in 100% polyethylene eliminates leaks and is nearly impervious to chemicals including acids and corrosives. Sturdy, self-locating grates eliminate the chance of ride-up and remove for easy cleaning.



Gator® Accumulation Centers

	Product	Sump Cap.	Load Bearing	Outside Dim.		
	Description	Gallons	Capacity Lbs (kgs)	W x D x H (mm)	Compliance	Model No.
3	1 drum unit	12.5/47L	1200 (544)	25" x 25" x 5 ¹ /2"(635 x 635 x 140)	-	28940
	2 drum unit	22/83L	2400 (1089)	49" x 25" x 5 ¹ /2"(1245 x 635 x 140)	-	28922
	4 drum unit	43/163L	6000 (2722)	49" x 49" x 5 ¹ /2"(1245 x 1245 x 140)	-	28923
	6 drum unit	64/242L	7000 (3175)	73" x 49" x 5 ¹ /2"(1854 x 1245 x 140)	EPA	28924
	8 drum unit	85/322L	8000 (3629)	97" x 49" x 5 ¹ /2"(2464 x 1245 x 140)	EPA	AK28905
	Ramp for size	s 2 drum and la	arger 1000 (454)	48" x 33" x 6 ¹ /4"(1219 x 838 x 159)	EPA,U	AK28906
	Joining clips, one pair, stainless steel			4" x 2"(102 x 51)	-	28926
				One pair stainless steel joining clips,		
	Sump-to-Sump [™] Drain Kit		one pa	one pair rubber grommets, one PTFE transfer tube		28927

*See page 8 for Regulation Key.



Strong and robust! Rotocast molded for a more

"blow molded" units

robust structure versus other

100