

# 8100

## Drench Showers



### FEATURES & BENEFITS

#### Shower Head

AXION MSR™ ABS plastic drench shower head uses a hydrodynamic design to give equal distribution of water throughout the entire footprint of flow.

#### Construction

1-1/4" Schedule 40 hot-dipped galvanized steel pipe and fittings along with powder-coated cast-iron 9" diameter floor flange provide corrosion resistance in a long lasting product.

#### Valve

Valve is designed so the full flow of water remains on with the simple tug of the triangular pull rod. Unit also comes equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage.

#### Pull Rod

28" stainless steel triangular pull rod provides a reachable height for users while maintaining its durable design.

#### Quality Control

Valve assembly is pre-built for reduced installation time and an added peace of mind for the end contractor.

#### Safety

8" x 10-3/4" universal emergency sign and 21" self-adhesive high visibility stripe in Safety Green and bright yellow make the 8100 easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.



### SPECIFICATIONS

Model 8100 floor mounted drench shower shall include the AXION MSR™ hydrodynamic designed green ABS plastic 10-5/8" shower head with integral self-regulating 20 gpm flow control, and chrome-plated brass stay-open ball valve equipped with a stainless steel ball and stem. Unit shall also include powder-coated cast-iron 9" diameter floor flange, self-adhesive high visibility 21" long stripe in Safety Green and bright yellow, stainless steel pull rod with triangular handle, universal sign, and 1-1/4" IPS supply.

### OPTIONS

- Model 8901RFK, body spray unit with AXION MSR™ eye/face wash head, stay open squeeze lever valve, 8-foot hose, and installation kit.
- Tempered Water Blending Systems: Model TWBS.SH is a prepackaged, fully engineered and tested system for mixing hot and cold water to provide tempered water up to 40 gpm for emergency shower and eyewashes (Pat.# 5,350,112).
- Tempered Water Blending Systems: Model 9202, is a thermostatic mixing valve that mixes hot and cold water for the tempering of shower units at a maximum flow rate of 40 gpm.
- Shower Head: Model 8127FC, corrosion-resistant 10-1/2" stainless steel shower head with integral 20 gpm flow control.

To see all options for this model, visit [www.hawasco.com](http://www.hawasco.com).

### APPLICATIONS

Where the body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching and cleansing of the body shall be provided within the work area for immediate emergency use. Emergency deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8100 is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.



# 8133H

Drench Showers



## FEATURES & BENEFITS

### Safety

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

### Construction

1" Schedule 40 stainless steel pipe and fittings provide corrosion resistance in a long lasting product.

### Flow Controls

Corrosion-resistant stainless steel showerhead with integral 20 gpm flow control provide an added protection in corrosive environments and an optimal water flow for the irrigation process.

### Valves

Type 316 Stainless Steel stay-open ball valve is designed so the full flow of fluid remains on with a simple tug of the pull rod and is equipped with a stainless steel ball and stem to provide extra protection against corrosion and breakage.

### Pull Rod

28" stainless steel triangular pull rod provides a reachable height for users while maintaining its durable design.

### Mounting

Designed for horizontal installation, this drench shower is mounted sturdily from any wall.

### Quality Control

Valve assembly is pre-built for reduced installation time and an added peace of mind for the installer.



## SPECIFICATIONS

Model 8133H horizontally mounted drench shower shall include a stainless steel 10-1/2" showerhead with integral self-regulating 20 gpm flow control, Schedule 40 Stainless Steel pipe and fittings, Type 316 Stainless Steel stay-open ball valve equipped with a stainless steel ball and stem, stainless steel pull rod with triangular handle, universal sign, and 1" IPS supply.

## OPTIONS

- Tempered Water Blending Systems: Model TWBS.SH is a prepackaged, fully engineered and tested system for mixing hot and cold water to provide tempered water up to 40 gpm for emergency shower and eyewashes (Pat.# 5,350,112).
- Tempered Water Blending Valves: Model 9202 is a thermostatic mixing valve that mixes hot and cold water for the tempering of shower units at a maximum flow rate of 40 gpm.
- Alarm: Model 9001, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by flow switch when emergency shower and eyewash are in use.
- Shower Test Kit: Model 9010 shower test kit includes holding rod, upper corrosion-resistant ring to encircle the shower head, and Tyvek waterproof tunnel shaped tube to guide the water column to container or drain.

To see all options for this model, visit [www.hawsc.com](http://www.hawsc.com).

## APPLICATIONS

Where the body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching or cleansing of the body shall be provided within the work area for immediate emergency use. Emergency eyewash facilities and deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8133H is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.



# 8122

## Drench Showers



### FEATURES & BENEFITS

#### Shower Head

AXION MSR™ 10-5/8" ABS plastic drench shower head uses a hydrodynamic design to give equal distribution of water throughout the entire footprint of flow.

#### Construction

1" Schedule 40 hot-dipped galvanized steel pipe and fittings provide a strong durability in a long lasting product.

#### Valve

Valve is designed so the full flow of water remains on with the simple tug of the triangular pull rod. Unit also comes equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage.

#### Pull Rod

28" stainless steel triangular pull rod provides a reachable height for users while maintaining its durable design.

#### Universal Mounting

Designed for horizontal or vertical installation, drench shower is mounted sturdily from any wall or ceiling.

#### Quality Control

Valve assembly is pre-built for reduced installation time and an added peace of mind for the end contractor.

#### Safety

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.



### SPECIFICATIONS

Model 8122 drench shower for horizontal or vertical installation shall include the Axion MSR™ hydrodynamic designed green ABS plastic 10-5/8" shower head with integral self-regulating 20 gpm flow control, chrome-plated brass stay-open ball valve equipped with a stainless steel ball and stem, stainless steel pull rod with triangular handle, universal sign, and 1" IPS supply.

### OPTIONS

- Model 8901RFK, body spray unit with AXION MSR™ eye/face wash head, stay open squeeze lever valve, 8-foot hose, and installation kit.
- Tempered Water Blending Systems: Model TWBS.SH is a prepackaged, fully engineered and tested system for mixing hot and cold water to provide tempered water up to 40 gpm for emergency shower and eyewashes (Pat.# 5,350,112).
- Tempered Water Blending Systems: Model 9202, is a thermostatic mixing valve that mixes hot and cold water for the tempering of shower units at a maximum flow rate of 40 gpm.
- Shower Head: Model 8127FC, corrosion-resistant 10-1/2" stainless steel shower head with integral 20 gpm flow control.

To see all options for this model, visit [www.hawsco.com](http://www.hawsco.com).

### APPLICATIONS

Where the body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching and cleansing of the body shall be provided within the work area for immediate emergency use. Emergency deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8122 is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.



# 8164

## Drench Showers



### FEATURES & BENEFITS

#### Safety

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

#### Flow Controls

High polished stainless steel showerhead with integral 20 gpm flow control provide an added protection in highly corrosive environments and an optimal water flow for the irrigation process.

#### Valves

Brass stay-open ball valve is designed so the full flow of water remains on with the simple tug of a pull down lever. Unit also comes equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage.

#### Pull Rod

Pull down lever is mounted within a recessed stainless steel wall cabinet for easy locating while providing a finished look.

#### Quality Control

Valve assembly is pre-built for reduced installation time and an added peace of mind for the installer.



### OPTIONS

- Tempered Water Blending Systems: Model TWBS.SH is a prepackaged, fully engineered and tested system for mixing hot and cold water to provide tempered water up to 40 gpm for emergency shower and eyewashes (Pat.# 5,350,112).
- Tempered Water Blending Valves: Model 9202 is a thermostatic mixing valve that mixes hot and cold water for the tempering of shower units at a maximum flow rate of 40 gpm.
- Alarm: Model 9001EXP 120 VAC Class 1, Division 2, Groups B, C, and D emergency alarm system. Buzzer and flashing light are activated by the 1-1/4" flow switch when emergency shower or eyewash is in use.
- Alarm: Model 9001, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by flow switch when emergency shower and eyewash are in use.

To see all options for this model, visit [www.hawsco.com](http://www.hawsco.com).

### SPECIFICATIONS

Model 8164 flush ceiling mounted drench shower shall include a high-polished stainless steel 10-5/8" showerhead with integral self-regulating 20 gpm flow control mounted in or hanging down from the ceiling, brass stay-open ball valve equipped with stainless steel ball and stem, recessed stainless steel wall cabinet with pull down lever, universal sign, and 1" IPS supply.

### APPLICATIONS

Where the body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching or cleansing of the body shall be provided within the work area for immediate emergency use. Emergency eyewash facilities and deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8164 is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.

