UNO® The easiest-to-use Safety Can with improved ergonomics for pouring!

For comfortable handling and safe, smooth, accurate pouring, nothing beats the UNO® can. It is perfect for repetitive use applications to reduce worker strain and fatigue.

UNO's exclusive "one-spout" design features a Safe-Squeeze® trigger mechanism that offers a highly controlled liquid flow method. As the can is tipped during pouring, the comfortable rounded handle rests firmly in the palm of your hand leaving your fingers free to gently squeeze the trigger and begin the flow of liquid. The bottom of the can is safely supported with your fingers using the ¹/₂" (13mm) grip lip at the bottom. As the trigger is engaged, the piston-actuated spout and vacuum release valve open

simultaneously for accurate, glug-free pouring.

For easy filling, simply engage the lift-latch with your finger and push down on the trigger to open the fill spout. A full length flame arrester allows full, secure insertion of gas nozzle.

In addition to meeting your ease-of-use and perform-

ance needs, UNO's built-in safety features include an internal dual-density flame arrester to dissipate heat and prevent flashback ignition; a leaktight, selfclosing lid; automatic venting between 3 and 5 psig (0.2 and 0.35 bar) to guard against pressure buildup at elevated temperatures and potential

explosion; and each and every can is 100% tested to guarantee leakproof construction. The flexible metal hose provides a grounding path to prevent static sparks when a

Complies with **OSHA & NFPA** requirements. Accepted container under CARB. FM approved; UL & ULC listed.



grounding wire is used.

A comfortable squeeze engages the vacuum release valve and allows the liquid to flow through the flexible hose for accurate, glug-free pouring. Release the handle and the valve instantly closes to guard against spills.

Easy to Fill!

One smooth action engages the lift latch and opens the self-closing spout wide for easy filling. A full length flame arrester dissipates heat and allows deeper, secure insertion of the nozzle when filling.







- Spring-loaded, self-closing fill spout controls vapors and automatically closes after filling or pouring to guard against dangerous spillage.
- Lift latch engages trigger to open the spout wide.
- Safe-Squeeze® trigger assures safe and easy control of liquid flow.

Patent: US 6.772.918 B2



oil additives for two cycle engines

UNO® ...the only Type II can with a patented "one spout" design

