



## Temporary Berm Seals Off Spills From The Environment, Nearby Drains And Doorways



Part# 2100

- Standard 10-foot sections can be cut to various lengths to meet custom needs.
- Unique, urethane material “weeps” into small cracks and crevices to seal off liquid flow.
- Spill Berm is non-absorbing and is easily cleaned for repeated use.
- Applications include:
  - Spill response
  - Temporary secondary containment
  - Sealing off of doorways during washdown operations
- Flexible Ultra-Spill Berm will bend and turn to form almost any shape while temporarily “bonding” to any smooth surface.
- **Helps comply with NPDES and SPCC.**

*Decide what shape or configuration is required and use optional Connectors and 90° Corners to complete the area.*



ULTRA-SPILL BERM
Part# 2100: Orange • Part# 2050: Black
Dimensions: 10'x4" x 1/4" (3,048 mm x102 mm x8 mm)
Weight: 31 lbs. per unit (14 kg)
Material: Non-absorbing polyurethane
Optional Connectors (Part# 2101) used to connect 10' (3,048 mm) sections
Optional Corners (Part# 2102) are used with Connectors to make 90° corners
Optional Carrying Case (Part# 2104)



U.S. Patent No. 5,236,281



## Taller Spill Berm Helps Contain or Divert Larger Volume Spills

- Flexible polyurethane construction is non-absorbent and chemical resistant — easily cleans with soap and water for repeated uses.
- Built-in connectors allow multiple 5-foot units to be quickly and easily connected.
- **Helps comply with NPDES and SPCC.**

ULTRA-SPILL BERM PLUS
Part# 2054
Dimensions: 5'x4" x 1/2" (1,524 mm x102 mm x14 mm)
Weight: 16 lbs. (7 kg) per unit
Material: Non-absorbing polyurethane

U.S. Patent No. 5,236,281



Part# 2054

