

# Flammable Liquid Safety Storage Cabinets

Capacity	W x D x H	No. of Shelves	Cat. No. Manual-Closing	Cat. No. Self-Closing	Cat. No. Extra Shelf	Cat. No. Mounting Brackets
<b>Standard</b>						
30 gal.	43 x 18 x 44"	one	5440N	5441N	5449N	n/a
45 gal.	43 x 18 x 65"	two	5444N	5445N	5449N	n/a
60 gal.	32 x 32 x 65"	two	5460	5461	5450	n/a
<b>Compact</b>						
4 gal.	17 x 17 x 22"	one	5470	n/a	5478	5480
12 gal.	23 1/4 x 18 x 35"	one	5473	n/a	5476	
12 gal.	43 x 18 x 18"	—	5471	n/a	—	5479
15 gal.	23 1/4 x 18 x 44"	one	5474	n/a	5476	
17 gal.	43 x 18 x 24"	one	5472	n/a	5449	5479
17 gal.	43 x 18 x 24"	one	5465*	n/a	5449	INCLUDED
20 gal.	43 x 12 x 44"	two	5466*	n/a	5477	INCLUDED
20 gal.	43 x 12 x 44"	two	5469	n/a	5477	5479
<b>Under-Counter</b>						
22 gal.	35 x 22 x 35"	one	5467	n/a	5468	n/a

## Technical/Ergonomic Features

- Conforms to NFPA Fire Code No. 30 and OSHA standards
- 1/2" shelf adjustment maximizes storage versatility inside cabinets.
- Ribbed, galvanized steel shelves deliver load capacity of 225 lbs. per shelf.
- All-welded, double wall construction (with 1 1/2" of insulating air space to offer fire resistant protection)
- Three-point latching system with key lock.
- Self-closing doors have fusible link that melts when ambient temperature reaches 160°, releasing the latch holding the door open.
- Screened flame arrester vents on both sides of cabinets are threaded to accept standard 2" pipe for external exhaust.
- Ground wire connection (wiring not included) deters static build-up.
- Zinc-plated leveling legs included.

*\*Includes brackets for wall-mounting.*

Polyethylene Shelf Tray for cabinet 5467: **No. 5567**  
 Polyethylene Bottom Tray for cabinet 5467: **No. 5568**

*Both trays include self-threading screws.*



Protect your employees and property with proper storage of flammable and hazardous liquids in the right cabinets and sizes for your workspace.

**Undercounter cabinet (5467)** has polyethylene shelf and bottom tray to contain inadvertent spills.



Dual 2" diameter threaded vents with fire baffle and cap provide for external exhaust.

Large warning labels!

Double wall, 18-gauge welded steel construction with 1 1/2" air space between walls offers fire resistance.

Baked on enamel Safety Yellow finish resists chipping, withstands hard knocks.

## Under-Counter Cabinets

### PRIMARY APPLICATIONS

- under-counter storage
- stand alone storage



5467  
22-Gallon

## Standard Cabinets

### PRIMARY APPLICATIONS

- stand alone storage
- as a base for stackable compact cabinets



SELF-CLOSING DOOR

18" DEEP MANUAL-CLOSING DOORS

5440N  
30-Gallon

5441N  
30-Gallon