

ALARMS



9001DPDT

Model 9001DPDT emergency alarm and light system features an amber flashing light and a 90 dB, at 10 feet, buzzer that is operated by a flow switch that incorporates an extra set of electrical contacts for remote alarm hook up. Unit is activated when the emergency shower or eyewash is in operation. System can be mounted to pipe or wall with optional wall bracket that is provided. It is recommended to install unit where a shower or eyewash is in a remote or noisy location where the user is unable to summon help. Voltage: 120 VAC, 50 or 60 cycles. Supply: 1 1/4" IPS.

Light and flow switch are UL Listed and CSA approved.



9001

Model 9001 emergency alarm and light system features an amber flashing light and 90 dB at 10 feet, buzzer that is operated by flow switch. Unit is activated when the emergency shower or eyewash is in operation. System can be mounted to pipe or wall with optional wall bracket that is provided. Unit is recommended to be installed where a shower or eyewash is installed in a remote or noisy location where user is unable to summon help. Lockable silencing switch ideal for testing unit. Voltage: 120 VAC, 50 or 60 cycles. Supply: 1 1/4" IPS. This alarm does not contain multiple sets of contacts for remote activation alarm sites.

Light and flow switch are UL Listed and CSA approved.



9001EXP

Model 9001EXP explosion-proof Class I, Div 2, Group B, C, D emergency alarm and light system features a red flashing light and 90 dB at 10 feet, buzzer that is operated by flow switch. Unit is activated when the emergency shower or eyewash is in operation. System can be mounted to pipe or wall with optional wall bracket that is provided. It is recommended to install unit where a shower or eyewash is in a remote or noisy location where user is unable to summon help. This alarm does not contain multiple sets of contacts for remote activation alarm sites. Voltage: 120 VAC, 50 or 60 cycles. Supply: 1 1/4" IPS.

Light and flow switch are UL Listed and CSA approved.



SP154

Model SP154 is a flow switch for use with the 9001 and 9001EXP alarms. AC, 125/250 volts, 5 amps, single pole, double-throw. 1 1/4" FIPS inlet and outlet. Class I, Div 1, Group B, C, D explosion-proof.

Flow switch is UL Listed and CSA approved.