

Safety Cabinets FOR FLAMMABLES

Safety Cabinets



New!

Haz-Alert™ Reflective labeling provides high visibility in the dark under fire conditions or power outage when illuminated by a flashlight beam.

Patent Pending. Hazard warning in three languages.



Patented concealed self-close mechanism provides obstruction-free access to top shelf space. Self-indexing doors guarantee they will close in sequence and assure a tight closure from top to bottom (on self-close models).



Fusible links hold doors wide open and melts at 165°F (74°C) for automatic closure (on self-close models).

Minimal air-gaps provide better protection.

Sturdy, 18-gauge (1mm) double wall steel with 1½" (38mm) of insulating air space.

Easy close, self-latching doors.

Fully-welded (not riveted) construction holds squareness for longer life, offering greater protection in a fire since air gaps are reduced.



Continuous piano hinge provides smooth closure.

Built-in grounding connector (on outside side panel) for easy grounding.

Dual vents with built-in flame arresters strategically placed at bottom and opposite top are welded, not screwed in place.

Durable and chemical resistant, hybrid lead-free powder coat paint finish, inside-and-out, retains high gloss look and minimizes the effects of corrosion and humidity.

Adjustable leveling feet for stability on uneven surfaces.



New!


Exclusive SpillSlope™ safety shelves direct spills to back and bottom of leak proof sump.

Heavy-gauge galvanized steel shelves are bi-directional and easily adjust on 3" (76mm) centers for versatile storage. Meet ANSI standards with a 350lb. (159kg.) safe allowable load. **Patent Pending**

2" (51mm) liquid-tight containment sump with up to a 5-gal. (19L) capacity on 45-gal. (170L) models, holds leaks and meets EPA requirements.



Welded shelf hangers interlock with shelf to offer maximum "no slip" stability... and no flimsy brackets to lose.



Rounded safety corners on doors reduce accidental nicks or cuts and potential hand injury.



890400

New!

Stainless steel, three-point bullet self-latching system provides easy, fail-safe, positive door closure with increased heat resistance.



New!

Exclusive U•Loc™ Padlockable Handle. Optional padlock* allows for extra security and keycoding multiples for convenient access. Flush paddle handle with slip resistant grip offers easy fingertip operation and reduces dangerous "catches" from passing traffic. Double key set included for keyed lock. **Patent Pending**

* Padlock sold separately



New!

Haz-Alert™ Safety Band. Firefighter friendly reflective band at bottom alerts firefighters when crawling in smoke-filled areas. **Patent Pending**



Complies with OSHA 29 CFR 1910.106 and NFPA Code 30, section 9.5

Most are FM approved
Shelves meet ANSI MH28.1