

Drum Storage Safety Cabinets



Horizontal Drum Storage Cabinet

Stores a single 55-gallon drum horizontally.

No. 5453

Vertical Drum Storage Cabinet

Safely houses one 55-gallon drum vertically.

No. 5451

Drum Ramp (optional)

- Facilitates the movement of drums in and out of the cabinet.
 - Attaches to the cabinet sill to prevent slippage.
 - Non-slip finish increases traction.
 - 10-gauge steel construction.
- 24 $\frac{7}{8}$ "w x 24" d x 2 $\frac{3}{4}$ "h

No. 5457

Vertical Drum Storage Cabinet

- Safely houses two 55-gallon drums.
- The fixed half-shelf leaves space for drums equipped with a pump or funnel.
- Will accommodate five 1-gallon cans and smaller containers.

No. 5452

Technical/Ergonomic Features

- Conforms to NFPA Fire Code No. 30 and OSHA standards
- Horizontal drum cabinet equipped with drum cradle guide rails.
- Ribbed, galvanized steel shelves deliver load capacity of 350 lbs. per shelf.
- Three-point latching system with key lock delivers secure closure to protect against fire and theft.
- Baked on enamel Safety Yellow finish resists chipping, withstands hard knocks.
- Vertical 1- and 2-drum cabinets come with drum supports inside to hold two 55-gallon drums and include a half-width shelf for additional can storage.
- Double wall, 18-gauge welded steel construction with 1 $\frac{1}{2}$ " air space between walls to offer fire proof protection.
- Dual 2" diameter threaded vents with fire baffle and cap provide for external exhaust.
- Ground wire connection (wiring not included) deters static build-up.
- Zinc-plated leveling legs included.



IMPORTANT:

NFPA Code 30 limits storage to 120 gallons per cabinet, including only 60 gallons of flammable liquids.



Drum Storage Accessories

Self-Closing Brass Drum Faucets



Brass Drum-Faucet 5506

- Designed for safe dispensing of flammable liquids from 30 and 55 gallon drums.
- Large lever-type handle regulates flow, closes automatically when lever is released.
- Built-in flash arresters and long lasting Teflon® O-Ring seals included.

No. 5506 – Self-Closing Faucet with Rigid Shank

No. 5507 – Adjustable Faucet with Swivel Spout



Grounding Wires 5508

Grounding Wires 5509

Bonding and Grounding Wire Assemblies

- Minimize Hazards of Static Electricity Buildup!
- Flexible plated steel wires allow electric charges to dissipate when grounded and bonded. (Required by OSHA during transfer of Class I liquids.)
- Connectors include 3 foot lengths of uninsulated wiring.

No. 5508 – Two Alligator Clip Connectors

No. 5509 – Two Hand Clamp Connectors