

SAFETY TRAX™

- **Sales Tip:** Be certain that primary surface area is completely dry and clean before applying the "peel & stick" backing or the optional Sealing Compound.
- **Where to Specify:** Inclines, ramped walkways.

- Slip resistant pads are affixed to surfaces to increase friction providing a safer pathway.
- Top surface is embedded with silicon carbide particles. As the particles wear, they chip into continuously aggressive finer particles that continue to provide function.
- Pressure adhesive backing allows for easy "peel and stick" installation.
- An optional edge sealing compound is recommended for applications exposed to water, grease or oil.



Black



#680 SAFETY TRAX™

Roll Sizes	1" x 60'	2" x 60'	3" x 60'	4" x 60'	6" x 60'	12" x 60'	24" x 60'
Weight (lbs.)	0.75	1.5	2	3	4	8	16

FULL CASE (50) ONLY

Custom Sizes & Full Cases	6" Width	12" Width	24" Width	5.5" x 5.5"	3/4" x 24"	6" x 24"
Weight (lbs.)	.15/sq.ft.	.15/sq.ft.	.15/sq.ft.	1.25	1.00	5.50

Edge Sealing Compound	5 oz. tube					
Safety Walk Primer*	Quart		*A Hazardous Material charge may be assessed by the freight carrier			

Shipping Location: Superior Manufacturing Group - Chicago, IL 60638

