

Acids and Corrosives Safety Storage Cabinets

Technical/Ergonomic Features

- Conforms to NFPA Fire Code No. 30 and OSHA standards
- 1/2" shelf adjustment maximizes storage versatility inside cabinets.
- Flanged, galvanized steel shelves deliver load capacity of 225 lbs. per shelf.
- Double-wall, 18-gauge welded steel construction with 1 1/2" of insulating air space between walls.
- Three-point latching system with key lock.
- Self-closing doors have fusible link that melts when ambient temperature reaches 160°, releasing the latch holding the door open.
- Ground wire connection (wiring not included) deters static build-up.
- Screened flame arrester vents on both sides of cabinets are threaded to accept standard 2" pipe for external exhaust.
- Zinc-plated leveling legs included.



Capacity	W x D x H	No. of Shelves	No. of Trays	Cat. No. Manual-Closing	Cat. No. Self-Closing	Cat. No. Extra Galv. Shelf	Cat. No. Extra Poly Shelf Tray	Cat. No. Extra Poly Bottom Tray	Cat. No. Mounting Brackets
Standard									
30 gal.	43 x 18 x 44"	one	two	5540	5541	5449N	5549	5550	n/a
45 gal.	43 x 18 x 65"	two	three	5544	5545	5449N	5549	5550	n/a
Compact									
12 gal.	43 x 18 x 18"	—	one	5591	n/a	5449N	—	5550	5479
17 gal.	43 x 18 x 24"	one	two	5592	n/a	5449N	5549	5550	5479
17 gal.	43 x 18 x 24"	one	two	5565*	n/a	5449N	5549	5550	INCLUDED
20 gal.	43 x 12 x 44"	five	six	5566*	n/a	5477	5551	5552	INCLUDED
20 gal.	43 x 12 x 44"	five	six	5569	n/a	5477	5551	5552	5479
Under-Counter									
22 gal.	35 x 22 x 35"	one	two	5595	n/a	5468	5567	5568	n/a

NOTE: NOT RECOMMENDED FOR PHENOL, SULFURIC OR NITRIC ACIDS.

**Includes brackets for wall-mounting.*

Undercounter and compact cabinets give you the flexibility to meet those special storage needs that cannot be fulfilled with standard 30, 45 or 60 gallon cabinets. Sometimes shorter or narrower or higher or lower is just right!



Replaceable, leakproof 2" deep polyethylene trays contain spills on all acid and corrosive models.

