## Protect Curb Inlets From Sediment-Laden Stormwater Runoff



Modular design allows units to be connected to make any length desired (3 units shown).

- Qck and easy installation.
- Modular design build to any length.
- Units can be quickly and easily connected to form longer lengths.
- Mige-shaped, heavy-duty foam secures unit in curb inlet.
- Wen, polypropylene material provides high flow rate — will not cause ponding or flooding.
- Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements.

U.S. Patent Pending

ULTRA-CUREGUARD PLUS		
Part# 9248	Dimensions: 4" dia. x 36" L (102 mm x 915 mm)	
Part# 9251	Dimensions: 4" dia. x 48" L (102 mm x 1,220 mm)	

## Ultra Curb Guard, Insert-Style



Patent No. 6,811,708

ULTRA-CUREGUARD, INSERT-STYE				
Part# 9760	Ultra-Curb Guard, Insert-Style	Fits 22"-35" (559 mm x 889 mm) inlets		
Part# 9761	Ultra-Curb Guard, Insert-Style	Fits 36"-60" (915 mm x 1,524 mm) inlets		

## **Keep Oil, Sediment, Floatables And Other Contaminants Out** Of Curb Inlets

- For use in drains with curb inlets only.
- Two heavy-duty tension rods keep unit secured inside inlet for a clean, flush-mounted installation.
- Filtering material is quickly and easily replaced.
- Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements.

