1107LBP

Wall Mounted Drinking Fountain



FEATURES & BENEFITS

Front Access

With its patented (Pat.# 6,981,692) push-button valve assembly which allows for front access stream adjustment as well as cartridge and strainer access, this fountain offers the ultimate in ease of maintenance.

Antimicrobially Treated

Specific components are antimicrobially treated using the natural protection of silver. Silver helps protect against the growth of mold and mildew on the treated components. Treated surfaces include bubbler head, push button, waste strainer and trap.

Access

Low profile designed bowl and integral trap that is set back for knee clearance allows for adult or child ADA access (when installed at appropriate heights).

Finish

Beautiful #4 satin stainless steel finish basin can be easily cleaned and maintained while also resisting corrosion.

Quality Control

Fountain is pre-built and fully water and pressure tested to ensure no leaks and proper function for reduced installation time and added peace of mind.

Integrated Trap

Spacious fountain design allows for the trap to be internally mounted which allows for easy access, and aids and reduces the installation process.

Construction

Heavy-duty 14 gauge Type 304 Stainless Steal construction with integral $\frac{1}{4}$ " mounting plates for extra durability. Unit also includes vandal-resistant bottom plates for added peace-of-mind.

Bubbler Head

Polished chrome-plated brass bubbler head features an integral basin shank for added strength, and is equipped with a shielded, anti-squirt orifice that provides a steady sanitary source of water.

OPTIONS

- □ Bubbler Head: Model 5725 EnviroGard™ bubbler is a polished chrome-plated solid brass bubbler head with stainless steel water activated pop up canopy. (Pat.# 7,025,282)
- □ Filter: Model 6426, 12" x 2", in-line lead removal element that reduces lead from incoming water supply.
- Mounting: Model 6700 universal mounting plate shall include a 3/16" steel pre-drilled and threaded mounting plate along with all-thread studs, nuts, and washers for use with many Haws single bubbler fountains.
- □ Support Carrier: Model 6800 universal support shall include dual 3/32" steel tube supports with integral 3/16" steel mounting feet along with u-bolts and hardware.

To see all options for this model, visit www.hawsco.com.



SPECIFICATIONS

Model 1107LBP wall mounted barrier-free drinking fountain shall include a 14 gauge Type 304 Stainless Steel satin finish basin with back panel and integral ¼" stainless steel mounting plate, antimicrobially treated push-button, bubbler head, waste strainer and trap to protect against the growth of mold and mildew on the treated components. Push-button operated valve with front-accessible cartridge and flow adjustment, polished chrome-plated brass vandal-resistant bubbler head, polished chrome-plated brass vandal-resistant waste strainer, vandal-resistant bottom plate, and a 1-1/4" IPS internal trap. Unit can be mounted to meet ADA or Child ADA specifications.

APPLICATIONS

Perfect for schools, airports, shopping malls and other high traffic areas. When installed properly, the heavy-duty, low profile design of the 1107LBP meets all current Americans with Disabilities Act requirements while providing an integrated trap that is ideal for quick installation, and can easily be installed on concrete or solid walls eliminating the need to provide "in-wall" trap access. The vandal-resistant bottom plate and 1/4" integral mounting plate also bring added peace of mind.







1109.14

Wall Mounted Drinking Fountain



FEATURES & BENEFITS

Front Access

With its patented (Pat.# 6,981,692) push-button valve assembly which allows for front access stream adjustment as well as cartridge and strainer access, this fountain offers the ultimate in ease of maintenance.

Construction

Heavy-duty 14 gauge Type 304 Stainless Steal construction with integral $\mbox{$\mathcal{Y}$}$ " mounting plates for extra durability. Unit also includes vandal-resistant bottom plates for added peace-of-mind.

Bubbler Head

Polished chrome-plated brass bubbler head features an integral basin shank for added strength, and is equipped with a shielded, anti-squirt orifice that provides a steady sanitary source of water.

Integrated Trap

Spacious fountain design allows for the trap to be internally mounted which allows for easy access, and aids and reduces the installation process.

Quality Control

Fountain is pre-built and fully water and pressure tested to ensure no leaks and proper function for reduced installation time and added peace of mind.

Finish

Beautiful #4 satin stainless steel finish basin can be easily cleaned and maintained while also resisting corrosion.

OPTIONS

- □ Bubbler Head: Model 5725 EnviroGard™ bubbler is a polished chrome-plated solid brass bubbler head with stainless steel water activated pop up canopy. (Pat.# 7,025,282)
- ☐ Filter: Model 6426, 12" x 2", in-line lead removal element that reduces lead from incoming water supply.
- □ Mounting: Model 6700 universal mounting plate shall include a 3/16" steel pre-drilled and threaded mounting plate along with all-thread studs, nuts, and washers for use with many Haws single bubbler fountains.

To see all options for this model, visit www.hawsco.com.



SPECIFICATIONS

Model 1109.14 is a wall mounted, barrier-free drinking fountain with 14 gauge Type 304 Stainless Steel with satin finish. It includes a push-button valve, polished chrome-plated brass bubbler head and waste strainer, integral 1/4" stainless steel mounting plate, vandal-resistant bottom plate and 1-1/4" NPT trap.

APPLICATIONS

Perfect for either public or private indoor/outdoor settings, Model 1109.14 is a great fit in areas where aesthetics are important to the overall appeal of the architecture. Suitable in areas where extra durability is needed, thicker gauged steel is implemented so this unit mounts solidly from any wall. Beautiful satin finish helps to maintain the fountains overall appeal so it always remains looking as new as it did when it was installed. Specifically, this type of wall mounted drinking fountain may be placed in settings such as: schools and other locations in and around office buildings where the temperature remains above freezing.







1117L

Wall Mounted Drinking Fountain



FEATURES & BENEFITS

Front Access

With its patented (Pat.# 6,981,692) push-button valve assembly which allows for front access stream adjustment as well as cartridge and strainer access, this fountain offers the ultimate in ease of maintenance.

Antimicrobially Treated

Specific components are antimicrobially treated using the natural protection of silver. Silver helps protect against the growth of mold and mildew on the treated components. Treated surfaces include bubbler head, push button, waste strainer and trap.

Configurable

Supplied with a low profile bowl, individual adjustable panels, and multiple mounting positions, this fountain can be configured for adult and child ADA considerations.

Quality Control

Both fountains are pre-built and fully water and pressure tested to ensure no leaks and proper function for reduced installation time and added peace of mind.

Back Panel

Stainless steel back panel helps to protect the wall from inadvertent splashing, and its decorative satin finish increases location visibility and completes the fountains attractive appearance.

Integrated Trap

Spacious fountain design allows for the trap to be internally mounted which allows for easy access, and aids and reduces the installation process.

Construction

Heavy-duty 14 gauge Type 304 Stainless Steal construction with integral $\frac{1}{4}$ " mounting plates for extra durability. Unit also includes vandal-resistant bottom plates for added peace-of-mind.

Bubbler Head

Polished chrome-plated brass bubbler head features an integral basin shank for added strength, and is equipped with a shielded, anti-squirt orifice that provides a steady sanitary source of water.

OPTIONS

- □ Bubbler Head: Model 5725 EnviroGard™ bubbler is a polished chrome-plated solid brass bubbler head with stainless steel water activated pop up canopy. (Pat.# 7,025,282)
- □ Filter: Model 6426, 12" x 2", in-line lead removal element that reduces lead from incoming water supply.
- □ Support Carrier: Model 6800 universal support shall include dual 3/32" steel tube supports with integral 3/16" steel mounting feet along with u-bolts and hardware.
- □ Chiller: Model HCR8, chiller provides for instantaneous cooling to meet a continuous demand for chilled water.



SPECIFICATIONS

Model 1117L low profile "Hi-Lo" wall mounted barrier-free drinking fountain shall include dual 14 gauge Type 304 Stainless Steel satin finish basins with integral 1/4" stainless steel mounting plates, antimicrobially treated push-button, bubbler head, waste strainer, and trap to protect against the growth of mold and mildew on the treated components. Push-button operated valves front-accessible cartridge and flow adjustment, polished chrome-plated brass vandal-resistant bubbler heads, polished chrome-plated brass vandal-resistant waste strainers. vandal-resistant bottom plates, stainless steel satin finish back panel, adjustable mounting allowing either basin high or low, in-wall mounting plate, and 1-1/4" IPS integral traps. Unit can be mounted to meet ADA or Child ADA specifications.

APPLICATIONS

Perfect for either public or private indoor/outdoor settings, Model 1117L is a great fit in areas where aesthetics are important to the overall appeal of the architecture. This series is precisely mounted, making it a nice addition to any surrounding. Beautiful satin finish helps to maintain the fountains overall appeal so it always remains looking as new as it did when it was installed. Specifically, this type of wall mounted drinking fountain may be placed in settings such as: schools and other locations in and around office buildings where the temperature remains above freezing.







1119.14

Wall Mounted Drinking Fountain



FEATURES & BENEFITS

Integrated Trap

Spacious fountain design allows for the trap to be internally mounted which allows for easy access, and aids and reduces the installation process.

Finish

Beautiful #4 satin stainless steel finish basin can be easily cleaned and maintained while also resisting corrosion.

Quality Control

Both fountains are pre-built and fully water and pressure tested to ensure no leaks and proper function for reduced installation time and added peace of mind.

Back Panel

Stainless steel back panel helps to protect the wall from inadvertent splashing, and its decorative satin finish increases location visibility and completes the fountains attractive appearance.

Barrier-Free

Barrier-free capabilities combined with its ease of use allows for a number of installation location possibilities.

Front Access

With its patented (Pat.# 6,981,692) push-button valve assembly which allows for front access stream adjustment as well as cartridge and strainer access, this fountain offers the ultimate in ease of maintenance.

Construction

Heavy-duty 14 gauge Type 304 Stainless Steal construction with integral $\ensuremath{\mathcal{V}}$ " mounting plates for extra durability. Unit also includes vandal-resistant bottom plates for added peace-of-mind.

Bubbler Head

Polished chrome-plated brass bubbler head features an integral basin shank for added strength, and is equipped with a shielded, anti-squirt orifice that provides a steady sanitary source of water.

OPTIONS

- □ Bubbler Head: Model 5725 EnviroGard™ bubbler is a polished chrome-plated solid brass bubbler head with stainless steel water activated pop up canopy. (Pat.# 7,025,282)
- ☐ Filter: Model 6426, 12" x 2", in-line lead removal element that reduces lead from incoming water supply.
- Cane Touch Skirt: Model SK1, satin finish stainless steel cane touch skirt for installation on high unit to comply with ADA protruding objects guidelines.
- Mounting: Model 6700.4 "Hi-Lo" universal mounting plate shall include a 3/16" steel pre-drilled and threaded mounting plate along with all-thread studs, nuts, and washers for use with many Haws dual bubbler fountains

To see all options for this model, visit www.hawsco.com.



SPECIFICATIONS

Model 1119.14 "Hi-Lo" wall mounted barrier free drinking fountain shall include dual 14 gauge Type 304 Stainless Steel satin finish basins with integral 1/4" stainless steel mounting plates, push-button operated valves with front-accessible cartridge and flow adjustment, polished chrome-plated brass vandal-resistant bubbler heads, polished chrome-plated brass vandal-resistant waste strainer, vandal-resistant bottom plate, stainless steel satin finish back panel, high and low fountain mounting levels, and 1-1/4" IPS traps.

APPLICATIONS

Perfect for either public or private indoor/outdoor settings, heavy-duty Model 1119.14 is a great fit in areas where aesthetics are important to the overall appeal of the architecture. Suitable in areas where extra durability is needed, thicker gauged steel is implemented so this unit mounts solidly from any wall. Beautiful satin finish helps to maintain the fountains overall appeal so it always remains looking as new as it did when it was installed. Specifically, this type of wall mounted drinking fountain may be placed in settings such as: schools and other locations in and around office buildings where the temperature remains above freezing.







1119FR

Wall Mounted Drinking Fountain



FEATURES & BENEFITS

Bubbler Head

Polished chrome-plated brass bubbler head features an integral basin shank for added strength, and is equipped with a shielded, anti-squirt orifice that provides a steady sanitary source of water.

Back Panel

Stainless steel back panel helps to protect the wall from inadvertent splashing, and its decorative satin finish increases location visibility and completes the fountains attractive appearance.

Barrier-Free

Barrier-free capabilities combined with its ease of use allows for a number of installation location possibilities.

Construction

18 gauge Type 304 Stainless Steel construction with vandal-resistant bottom plates provides a long lasting unit with added peace of mind.

Finish

Beautiful #4 satin stainless steel finish basin can be easily cleaned and maintained while also resisting corrosion.

All-Weather Capabilities

Fully engineered system with the pneumatic operated freeze-resistant valve installed on the inside wall where room temperature does not drop below 50°F. When valve goes to off position, water left in supply line between valve and bubbler drains back into waste inside cabinet, which allows fountain on outside to function year-round.

OPTIONS

- Cane Touch Skirt: Model SK1, satin finish stainless steel cane touch skirt for installation on high unit to comply with ADA protruding objects guidelines.
- □ Mounting: Model 6700.4 "Hi-Lo" universal mounting plate shall include a 3/16" steel pre-drilled and threaded mounting plate along with all-thread studs, nuts, and washers for use with many Haws dual bubbler fountains
- Support Carrier: Model 6800 universal support shall include dual 3/32" steel tube supports with integral 3/16" steel mounting feet along with u-bolts and hardware.

To see all options for this model, visit www.hawsco.com.



SPECIFICATIONS

Model 1119FR "Hi-Lo" wall mounted barrier-free freeze-resistant drinking fountain shall include dual 18 gauge Type 304 Stainless Steel satin finish basins, polished chrome-plated brass vandal-resistant bubbler heads, polished chrome-plated brass push-buttons which operate pneumatic valves installed on the inside wall where room temperatures do not drop below 50°F, self-draining water lines protect the unit from freezing, polished chrome-plated brass vandal-resistant waste strainers, stainless steel satin finish back panel, high and low fountain mounting levels, and 1-1/4" O.D. waste pipes.

APPLICATIONS

Perfect for either public or private outdoor settings, Model 1119FR is a great fit in areas where aesthetics are important to the overall appeal of the architecture. This series is precisely mounted, making it a nice addition to any surrounding. Beautiful satin finish helps to maintain the fountains overall appeal so it always remains looking as new as it did when it was installed. Specifically, this type of wall mounted drinking fountain may be placed in settings such as: parks, schools, and other facilities where the temperature may drop into freezing conditions.





