Avoid overfilling drums and dangerous "run-overs" with a Drum Fill Gauge.

Vertical Drum Polethylene Pop-up Gauge is a low cost solution to overfilling drums during waste disposal operations. When drum is almost full, indicator "pops-up" to warn you.

Horizontal Drum Cast-iron Fill Gauge allows you to easily check liquid level of a horizontal drum at a glance no more surprise re-orders or stock depletions. Use indoors or out. Sight gauge shows how much liquid remains in a 30- (110L) or 55-gallon (200L) drum.

Drum gauge installs easily by threading into a standard 3/4" NPT bung hole and accepts any 3/4" faucet.

Rugged zinc-plated, cast-iron body stands up to heavy use. Heavy gauge glass tubing is protected with a chrome-plated housing and permits use with non-viscous oils. Buna-N seals make this unit ideal for petroleum products.

08530

Drum Fill Gauges

Drum Equilibrium

Description	Dimensions	Model No.
Vertical drum polyethylene pop-up gauge	³ /4" dia 5"L (127mm)	08530
Vertical drum polyethylene pop-up gauge	³ /4" dia 11"L (279mm)	08531
Horizontal drum cast-iron fill gauge	³ /4" dia 11 ¹ /4"(286mm)	08532*
Herizontal drum cast iron fill gauge No. 08532 w	ith solf closing fauget No. 08002	08533

Horizontal drum cast-iron fill gauge No. 08532 with self-closing faucet No. 08902 Can be used with drum siphon adapter No. 08311 or self-closing faucet No. 08308 with drum siphon adapter No. 08311 (see page 111).

Reduce fire risks from

static electricity.

Antistatic Wires prevent sparks from static electricity generated by movement and flow of flammable liquids. Bonding between containers during liquid transfer, and connecting drums to an earth ground are required under Federal and Local Codes. Standard wire lengths are 3' (1M) and 10' (3M); for longer reach use several wires with 1/4" (6mm) terminal ends. Custom length bonding and grounding assemblies in 3' (1M) lengths are also available as are individual clamps.

08500

Flexible Wire Insulated Flexible Wire



08505

Model No.





08507



Description	End Connections
Flexible wire, 10' (3 meters) coiled	Hand clamp x 1/4"(6
Insulated wire, 10' (3 meters) coile	d Hand clamp x 1/4"(6
Flexible wire, 3' (1 meter)	"C" clamp 5/8"(16mr
Flexible wire, 3' (1 meter)	Dual hand clamps
Flexible wire, 3' (1 meter)	Dual alligator clips 5
Flexible wire, 3' (1 meter)	"C" clamp (5/8"(16m
Flexible wire, 3' (1 meter)	Dual 1/4"(6mm) term
Insulated wire, 3' (1 meter)	"C" clamp 5/8"(16m
Insulated wire, 3' (1 meter)	Dual 1/4"(6mm) term
Insulated wire, 3' (1 meter)	"C" clamp ⁵ /8"(16m

	Hand clamp x 1/4"(6mm) terminal	08496
d	Hand clamp x 1/4"(6mm) terminal	08497
	"C" clamp ⁵ /8"(16mm) x hand clamp	08498
	Dual hand clamps	08499
	Dual alligator clips ⁵ /8"(16mm) jaws	08500
	"C" clamp (⁵ /8"(16mm) x alligator clip ⁵ /8"(16mm)	08501
	Dual 1/4" (6mm) terminals. Also used as an extension	08503
	"C" clamp ⁵ /8"(16mm) x alligator clip ⁵ /8"(16mm)	08505
	Dual 1/4" (6mm) terminals. Also used as an extension	08506
	"C" clamp ⁵ /8"(16mm) x pipe clamp 2 ³ /4"(70mm) jaw	08507

08499



For custom assemblies, call Customer Service.

