

NIRU® CUSHION-EASE®
NIRU® CUSHION-EASE® SOLID

#650
#656

SAFETY / ANTI-FATIGUE • "WET/DRY" • SUPERIOR™



- **Sales Tip:** The amount of slip resistance required, and exposure to chemicals, oils, and greases are the key determining factors when choosing between GSII™ or Niru® Cushion-Ease® products
- **Where to Specify:** (650) Intended for harsh wet environments where industrial chemicals, oils, greases, and animal fats are often found. (656) should be recommended for industrial applications where exposure to chemicals, oils, greases, and animal fats can create slip hazards.

- 100% Nitrile rubber compound provides the highest degree of resistance to chemicals, oils, and greases
- Available in perforated (650), or solid top (656) versions
 - 650 has a large hole drainage system that facilitates the removal of liquid and debris from the work area
 - 656 offers solid-top construction for additional anti-fatigue relief, and is easy to clean
- Overall thickness is 3/4"
- Modular design is compatible with NoTrax® 551 M.D. Ramp System and can accommodate a variety of custom configurations (see page 24 for more information)



RESULTS from INDEPENDENT TEST LABS & PRESENTED as COMPARISONS to OTHER NOTRAX® INDUSTRIAL MATS



Part of the Solutions™ product line. See pages 30 – 31 for details.

Solutions™
 BY NOTRAX®

#650/656 Niru® Cushion-Ease® Solid		
Stock Size	3' x 3'	3' x 5'
Weight (lbs.) #650	23	40
Weight (lbs.) #656	29	N/A
Shipping Location: Superior Manufacturing Group - Chicago, IL 60638		



#650