Darley Heat Exchanger

Can be installed in the engine cooling system of any pumper. Instead of going directly into the engine cooling system, mixing with the anti-freeze solution, diluting it and then going out through the radiator overflow pipe, the flow of cool water from the pump bypasses through the condenser coils in the Heat Exchanger. The liquid in the cooling system circulates around the condenser coils and is completely cooled. Prevents loss of anti-freeze solution. 24" long. Ship. wt. 10 lbs.



F618 Darley Heat Exchanger

Radiator Heat Exchanger Fits Between Radiator Hoses

Does the same job as our F618 Heat Exchanger but fits between the radiator hoses to make installation easier. Only additional connections required are tube lines from pump discharge to return line to suction side of pump. Measures 91/2" long.



Specify 13/4", 2" or 21/4"

\$249.95 R592A Radiator Heat Exchanger

Vernier Throttle Control

Easily installed throttle designed for apparatus. Provides both instant and micro meter fine adjustment together with a locking action which is not affected by vibration while pumping. The instant adjustment is conveniently made by a push-pull movement of the knob after a slight pressure is applied on the thumb button. The fine or Vernier adjustment is made by simply turning the same knob. Throttles are shipped complete, ready-to-install in 15' or 20' lengths. Ship. wt. 5 lbs.



F62101 15' Vernier Throttle \$44.95 F62103 20' Vernier Throttle \$50.95

Mattydale Swivel

Rugged cast brass elbow for use with mattydale hose beds. 11/2" NPT female free swivel inlet with 11/2" NST male outlet. Rough brass finish. Ship. wt. 4 lbs.



Magnesium Anode Pole

Attracts Rust & Corrosion

Sacrificial catalytic action of these magnesium anodes can help to prevent rust or corrosion from attacking your booster tank. Threaded mounting plate suspends the 3/4"x45" solid anode in the tank water. Bar is easily cut to fit tanks less than 44" deep. When the expendable anode dissolves, it is merely replaced with a new one. Comes with flange and gasket. Ship. wt. 3 lbs.

Mounting plate

\$52.95 Magnesium Anode Pole

Brass Swing Check Valves

Building your own apparatus? Swing check valves are a vital component in units that must prevent water or foam from the pump from reaching the water tank. All-brass heavy-duty construction. Ship. wt. 8 lbs.



U916	1" Brass Swing Check Valve	\$8.95
U917	11/2" Brass Swing Check Valve	\$18.95
U918	21/2" Brass Swing Check Valve	\$64.95
U919	3" Brass Swing Check Valve	\$100.95
U920	4" Brass Swing Check Valve	\$145.95

Darley Brass Valve

One-piece brass valve that withstands operating pressures to 3,000 psi. Needle type for accurate reading of pressure gauges. Opens completely in five turns. For use with pressure regulator, bypass, heat exchanger or in any location where a water control valve is necessary. 1/8" iron pipe tab. Ship. wt. 1 lb.

Easy-to-install

Darley Brass Valve \$32.95

1978 Aluminum Ball Valve

Ball valves feature rugged cast aluminum alloy body construction with acetale ball and nitrile seats. These valves are lightweight, field serviceable and are rated to 500 psi. You can be assured of a quality design at an affordable price. Ideal for drop-in units. Ship. wt. 2 lbs.

AIVI1/4 - Specity size						
Size	Inlet	Outlet	Waterway	Price		
1"	1"M	1"M	1"	\$128.95		
11/2"	1¹/₂"F	11/2"F	13/8"	\$134.95		
2"	2"F	2"F	13/8"	\$134.95		
21/2"	21/2"F	21/2"F	2"	\$185.95		
21/2"	21/2"F	$2^{1}/_{2}$ "M	2"	\$190.95		
11/2"	1¹/₂"F	11/2"M	13/8"	\$134.95		