Multipurpose use

Rechargeable

UL Rated 4-A, 60-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Home/Business unit is fitted with a pressure gauge that provides at-aglance status, cylinder is manufactured from impact resistant steel and the valve assembly is all metal.

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 10 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G)
 approved when fitted with mounting bracket (not supplied)
- Powder coated cylinder for corrosion protection
- U.S.C.G. approved bracket part number 366242



UPC: 0-47871-66031-5

At a Glance

- Model Home/Business
- Multipurpose Dry Chemical
- UL listed
- UL rated 4-A, 60-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Product Specification

For use on the following

types of fire:

| r rodact Specification | |
|------------------------------|------------------|
| Net agent weight (Average) | 10 lb |
| Unit weight (Average) | 16 lb |
| Diameter | 5.21 inches |
| Height | 19.52 inches |
| Discharge time | 19-21 seconds |
| Discharge range | 20 feet |
| Operating pressure | 195 psi |
| Cylinder | Mild steel |
| Valve, handle, lever | Aluminum |
| Strap Bracket (not supplied) | U.S.C.G approved |

Packaging Options





