

Fire Control Fire Extinguisher (FC340M-VB)

Part number 466425

Multipurpose use

Rechargeable

UL Rated 3-A, 40-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The FC340M-VB unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough metal valve assembly.

Supplied with metal retention bracket.

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- Powder coated cylinder for corrosion protection

At a Glance

- Model FC340M-VB
- Multipurpose Dry Chemical
- UL listed
- UL rated 3-A, 40-B:C
- Supplied with retention bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



UPC: 0-47871-66425-2

Product Specification

Net agent weight (Average)	5.0 lb.
Unit weight (Average)	7.9 lb.
Diameter	4.5 inches
Height	16.07 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK