

Badger

Fire Protection

Brigade Dry Chemical

Nitrogen Expellent Cartridge Models



The BRIGADE is the industry's most effective cartridge operated dry chemical fire extinguisher, incorporating standard features that go far beyond the "options" available on others' cartridge units.

The BRIGADE extinguisher offers the very best in fire fighting performance and usability. It is available with Multipurpose, Regular or Purple K Dry Chemical to meet any type of industrial fire hazard.

It is rapidly becoming the number one choice of the professionals especially when high hazard fires demand fast, effective and reliable response.

FEATURES

- Low temperature models are approved for use down to -65°F (-54°C)
- Available in three sizes - 10 lb, 20 lb and 30 lb
- "Standard" and "high flow" models for optimum fire fighting performance
- Fitted with low maintenance swivel discharge nozzle for both left and right handed operators.
- Designed with more extinguishing agent for higher fire ratings, longer range, extended discharge times and higher flow rates
- Permanent UL marking on the agent cylinder collar to allow for nameplate replacement in the field
- Indicator fill cap with offset sure-grip surface for easy removal
- Stainless steel cartridge guard and ring pins for extended life
- Heavy duty, corrosion resistant vehicle brackets
- Field replaceable nameplates

TYPICAL BRIGADE HIGH HAZARD APPLICATIONS:

- Petrochemical
- Mining
- Industrial
- Energy
- Transportation
- Utilities
- Forestry

All Brigade models feature deep drawn, seamless steel, corrosion resistant cylinders with full 360° attachment welds for added strength and corrosion resistance.

UL listed
USCG approved



Brigade Technical Specifications

	10 lb models			20 lb models					30 lb models				
MODEL	B-10-RG-LT	B-10-PK-LT	B-10-A-LT	B-20-RG-LT	B-20-PK-LT	B-20-PK-HF-LT	B-20-A-LT	B-20-A-HF-LT	B-30-RG-LT	B-30-PK-LT	B-30-PK-HF-LT	B-30-A-LT	B-30-A-HF-LT
Part Number	466525	466526	466524	466531	466532	466568	466530	466581	466540	466536	466583	466535	466582
Performance Type	Standard	Standard	Standard	Standard	Standard	High Flow	Standard	High Flow	Standard	Standard	High Flow	Standard	High Flow
Agent	Regular	Purple K	ABC	Regular	Purple K	Purple K	ABC	ABC	Regular	Purple K	Purple K	ABC	ABC
Agent Capacity (lbs.)	12	10.5	10.65	23	22	22	21	21	29	28.5	28.5	25	25
Agent Capacity (Kg)	5.44	4.76	4.83	10.43	9.98	9.98	9.53	9.53	13.15	12.93	12.93	11.34	11.34
UL Fire Rating	40 B:C	60 B:C	4A-40 B:C	60 B:C	80 B:C	20 B:C	20A-60 B:C	2A-40 B:C	120 B:C	120 B:C	40 B:C	20A-80 B:C	3A-40 B:C
USCG			Type A Size II				Type A Size II	Type A Size II				Type A Size II	Type A Size III
Approval	Type B:C Size II	Type B:C Size II	Type B:C Size II	Type B:C Size III	Type B:C Size III	Type B:C Size III	Type B:C Size III	Type B:C Size III	Type B:C Size IV	Type B:C Size IV	Type B:C Size IV	Type B:C Size III	Type B:C Size III
Discharge Time (sec.)	17-21	17-20	17-21	20-26	22-25	13	22-24	16	26-30	27-30	15	29-32	15
Agent Flow Rate (llb/sec.)	0.68	0.57	.65	1.12	1.02	1.96	1.05	1.58	1.03	.93	2.08	0.80	1.86
Agent Flow Rate (Kg/sec.)	0.31	0.26	0.29	0.50	0.46	0.89	0.48	0.72	0.47	0.42	0.94	0.36	0.84
Discharge Range (Feet)	15-25	15-25	15-25	15-30	15-30	15-30	15-30	15-30	15-35	15-35	15-35	15-35	15-35
Discharge Range (Meters)	4.57-7.62	4.57-7.62	4.57-7.62	4.57-9.14	4.57-9.14	4.57-9.14	4.57-9.14	4.57-9.14	4.57-10.67	4.57-10.67	4.57-10.67	4.57-10.67	4.57-10.67
Temperature Range (°F)	-65° TO +120°	-65° TO +120°	-65° TO +120°	-65° TO +120°	-65° TO +120°	-65° TO +120°	-65° TO +120°	-65° TO +120°	-65° TO +120°	-65° TO +120°	-65° TO +120°	-65° TO +120°	-65° TO +120°
Temperature Range (°C)	-54° TO +49°	-54° TO +49°	-54° TO +49°	-54° TO +49°	-54° TO +49°	-54° TO +49°	-54° TO +49°	-54° TO +49°	-40° TO +49°	-54° TO +49°	-54° TO +49°	-54° TO +49°	-54° TO +49°
Unit Height (Inches)	18.25	18.25	18.25	23.60	23.60	23.6	23.6	23.6	23.6	23.6	23.6	23.6	23.6
Unit Height (CM)	46.36	46.36	46.36	59.94	59.94	59.94	59.94	59.94	59.94	59.94	59.94	59.94	59.94
Unit Width (Inches)	9.5	9.5	9.5	11.25	11.25	11.25	11.25	11.25	12.25	12.25	12.25	12.25	12.25
Unit Width (CM)	24.13	24.13	24.13	28.58	28.58	28.58	28.58	28.58	31.12	31.12	31.12	31.12	31.12
Cylinder Diameter (Inches)	5.12	5.12	5.12	6.25	6.25	6.25	6.25	6.25	7.2	7.2	7.2	7.2	7.2
Cylinder Diameter (CM)	13	13	13	15.88	15.88	15.88	15.88	15.88	18.29	18.29	18.29	18.29	18.29
Shipping Weight (lbs.)	28	26.5	26.5	48.5	47.5	47.5	46.5	46.5	56	55.5	55.50	52	52
Shipping Weight (Kg)	12.7	12.02	12.02	22	21.55	21.55	21.09	21.09	25.40	25.17	25.17	23.58	23.58
USCG Bracket	B-10	B-10	B-10	B-20	B-20	B-20	B-20	B-20	B-30	B-30	B-30	B-30	B-30

BFPN0017

Nitrogen Expellent Cartridge Models

Badger

Fire Protection

4251 Seminole Trail
 Charlottesville, VA 22911
 Tel. (800) 446-3857
 Fax. (800) 248-7809
www.badgerfire.com