Residential Series

Living Area Fire Extinguisher (Primary Protection)

Part number 21005770

Living area use

Single use

UL Rated 2-A:10-B:C









Meets NFPA recommendations for primary home protection

For use on the following

types of fire:

Description

Fights fires common to the home living areas such as wood, fabrics, furnishings, and drapes.

Meets NFPA recommendations for primary home protection and has a 10 year warranty.

Features bilingual nameplate and carton.

White finish.

At a Glance

- Model FX210R
- Multipurpose Dry Chemical
- UL listed
- UL rated 2-A:10-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 10 year limited warranty

Product Specification

| Net agent weight (Average) | 4.0 lb. |
|----------------------------|-------------------|
| Unit weight (Average) | 7.13 lb. |
| Diameter | 4.5 inches |
| Height | 16.07 inches |
| Discharge time | 13-15 seconds |
| Discharge range | 12-18 feet |
| Operating pressure | 195 psi |
| Cylinder | Seamless aluminum |
| Valve, handle, lever | Nylon |
| Wall hanger | UL Listed |
| | |

Features

- Pressure gauge allows for immediate pressure status check
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 4 lb. of fire extinguishing agent (Average)
- 10 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection



UPC: 0-47871-05770-2

Packaging Options

Master Pack (2)
Master Pack (4)
Cut Case (8)

21005770 21005771 21005772





