

Calibrated Cap Gauges



Cap gauges are used for determining static or pressure on hydrant, pumpers or hoses. Complete with a petcock valve. Standard 0-300 psi gauge. *Ship. wt. 2 lbs.*

AW148	1 1/2" Calibrated Cap Gauge	\$158.95
AW149	2 1/2" Calibrated Cap Gauge	\$142.95

Calibrated In-line Gauges



All weather-calibrated gauges are used for testing static and pressure, designed to resist shock and vibration. *Ship. wt. 3 lbs.*

Specify Thread

AW150	1 1/2" Calibrated In-line Gauge	\$146.95
AW151	2 1/2" Calibrated In-line Gauge	\$202.95
AW152	4" Calibrated In-line Gauge	\$349.95

Ground Sweep Nozzle

Constant-flow fixed nozzles so we must know the gpm you want at 100 psi. Choose from 5 to 40 gpm (3/4") or from 40-100 gpm (1"). Pre-set at factory, easily field re-settable. Fog capability to 120°. *Ship. wt. 1 lb.*



Specify male or female NPT (Tapered)

Z321	Fixed Nozzle, 3/4"	\$132.95
Z322	Fixed Nozzle, 1"	\$174.95

Hydrant Cap

Use with Hydrant Conversion Bushing or use to replace lost or damaged caps. *Ship. wt. 1 lb.*



R475	2 1/2" Cap	\$36.95
R476	4 1/2" Cap	\$52.95

Hydrant Diffuser

Lightweight and easy to handle. 2" PVC body with ABS nut. 45° discharge will swivel 360°. *Thousands sold, 100% factory guarantee. Ship. wt. 1 lb.*

45° Discharge/ 360° Swivel

AW157	Hydrant Diffuser	\$43.95
-------	------------------	---------



Hydrant Flushing Elbow

Diverts the water force away from traffic or landscaping during periodic hydrant flushing. Available in 2 1/2", 4" or 4 1/2" female swivel connection. Brass connection with aluminum elbow. *Ship. wt. 5 lbs.*

Y807	Hydrant Flushing Elbow, 2 1/2" Thread	\$98.95
Y808	Hydrant Flushing Elbow, 4" Thread	\$184.95
U827	Hydrant Flushing Elbow, 4 1/2" NST	\$196.95

Hydrant Backflow Preventer



The Backflow Preventer is designed to provide protection of the safe drinking water in accordance with national plumbing codes and water utility authority requirements. They can be utilized in backflow prevention programs, including high hazard cross-connections in plumbing systems, or for containment at the service line entrance. Features two in-line, independent check valves with an intermediate relief valve. Standardly furnished with ball type test cocks.

2 1/2" NST x 2 1/2" NST

AW158	Hydrant Backflow Preventer	\$716.95
-------	----------------------------	----------

2.5" Hydrant Gate Valve

- ▶ High-strength, heat-treated, hard-anodized aluminum body
- ▶ Inlet swivel machined from 6061-T6 seamless aluminum extrusion hardcoat anodized to MIL-A-8625 Type III, Class 1
- ▶ Features a non-rising bronze stem with bronze gland, gate, nipple and seat
- ▶ Heavy-duty wedge with crank handle
- ▶ An excellent shutoff to control water hammer
- ▶ Less than 9 turns required to open or close



Open Pressurized Gates Slowly

BG264	2.5" Hydrant Gate Valve	\$283.95
-------	-------------------------	----------



Red Head
Brass, LLC