



Style #333  
Multi-Purpose Nozzle  
1.5" or 2.5" Inlet

## Features

- Providing The Combination of Solid Stream And Fog Pattern At The Same Time Or Independently
- Advantages Of Solid Bore Reach, Penetration, High Volume and Low Pressure Operation With Fog Protection And Cooling
- Solid Bore Stream To Fog Stream Without Shutdown
- Operate Efficiently At Pressure As Low As 50 PSI (3.5 BAR)
- Twist Shutoff Of The Fog Stream  
Ball Shutoff Of The **Straight Stream**
- Solid Bore Tip Available in 4 Different Size:
  - 3/4" (115 GPM or 435 LPM AT 50 PSI or 3.5 BAR)
  - 7/8" (155 GPM or 585 LPM AT 50 PSI or 3.5 BAR)
  - 15/16"(180 GPM or 685 LPM AT 50 PSI or 3.5 BAR)
  - 1"(205 GPM or 775 LPM AT 50 PSI or 3.5 BAR)
- Fog Stream Operation
  - 95 GPM(360 LPM) AT 50 PSI (3.5 BAR)
  - 135 GPM (510 LPM) AT 100 PSI (7 BAR)
  - PLUS FLUSH CAPABILITY**
- Infinite Patterns Detents For Positive Positioning
- CAFS Capability
- Suitable for Multiple Applications of Interior, Exterior, Foam, Penetration, Protection and Ventilation
- Weight: 6 Lbs Length: 10"