FireBreaker Fighting - Weight™ Boots

Tremendous physical exertion in extremely dangerous conditions is one of the reasons a firefighter's job is so unconventional. Add to that situation the impact of carrying up to 100 extra pounds of protective gear and equipment and it's easy to understand how fatigue can quickly impact safety and performance. Fatigue reduction is exactly why we designed the Firebreaker Fighting-Weight™ to be up to 25% lighter than heavier, conventional fireboots. Made with an exclusive Unishield™ process, a pair of Fighting-Weights™ still provides all the protection of the original Firebreaker, yet is lightweight enough so that the difference can truly be felt. Independent clinical studies reveal that reducing a pound of weight on the foot has the same stress-relieving benefit as taking five pounds off a firefighter's back. That means Fighting-Weight™ boots' lighter weight can translate to an eight-pound reduction off a firefighter's load when compared with the heaviest boots of other manufacturers. NFPA 1971 (2000 Edition) Compliant. Ship. wt. 7 lbs.

- Unishield™ innovative latex rubber dipping process eliminates seams, produces lighter-weight boots
- High abrasion-resistant outsole and heel
- Patented built-in shin guard
- ▶ FootGuard Protection System™
- AccuFit Sizing™ uses widely accepted Brannock device sizing
- ► Heavy insulation



Specify width and size

AJ540	Men's FireBreaker Fighting-Weight™ Trac Tread Outsole	\$135.95
AJ542	Men's FireBreaker Fighting-Weight™ Lug Outsole	\$145.95
AJ543	Women's Firebreaker Fighting-Weight™ Lug Outsole	\$145.95

Stormking Firefighter Boots

31" high. Available insulated or non-insulated. ANSI - American National Standard Z41-1999 OSHA - Occupational Safety/Health Admin. 1988 Code of Federal Registry 1910.36,1910.156 and Appendix E. CAL-OSHA - Calif. Admin code Title 8 GISO Article 10.1 Sept 1985. CSA - Canadian Standards Assoc. Master Contract #205043. Ship. wt. 9 lbs.

- Height 31"
- Vulcanized, layered rubber
- Upper Rubber formulation is fire-resistant, resists cracking and oxidation
- Lining 20 oz. grey felt
- Outsole White high-abrasion
- Dutsole pattern White Sure Loc™ outsole
- Heel Black molded rubber
- Heel reinforcement Cotton/nylon blend
- Insole 3/8" cushion sponge
- Steel toe Meets ANSI Z41 1999 Section 1 Impact & Compression
- Steel midsole One piece stainless steel
- Steel shank .05" x 1" x 4" triple ribbed
- Non-NFPA compliant
- Wide sizes only
- ► Whole sizes: 5-15





