

BADGER Extra Stored Pressure Hand Portables

# ABC Multipurpose Dry Chemical



A UTC Fire & Security Company

## Suitable for Class A, B and C fires

The Badger Extra multipurpose dry chemical line of fire extinguishers are economical and extremely versatile. They are ideal for tackling the majority of fire risks typically found in commercial, industrial and domestic applications.

Badger dry chemical extinguishing agent formulations contain the highest percentage of essential base ingredients found in the fire extinguisher industry. "Multipurpose" agent models are suitable for use on Class A, B and C fires.

Badger Extra models offer compliance and protection with premium features.

### Features:

- Multipurpose agent contains 90% M.A.P.
- Chrome plated brass valves
- Stainless steel handles, levers and hose bands
- Large loop stainless steel pull pins with tether
- Steel cylinder and internal siphon tubes
- Plated brass hose couplings with hex fitting
- Rugged, heavy-duty hoses
- UL Listed and USCG Approved—Meets D.O.T. requirements
- 12 year periodic hydrostatic test interval
- Six year warranty
- Easy-to-read two-piece nameplates



Badger Fire Protection  
944 Glenwood Station Lane, Suite 303, Charlottesville, VA 22901  
Tel.: 434.964.3200 • Fax: 434.964.3202 • [www.badgerfire.com](http://www.badgerfire.com)

## Technical Data:

# BADGER *Extra* ABC Multipurpose Dry Chemical Stored Pressure Extinguishers

MODEL	B250M-WH	B250M	B5M-B	B5M	B10M-1	B10M	B20M
PART NUMBER	23462	23384	23463	23390	23467	23396	23497
CAPACITY (lb.)	2.5	2.5	5	5	10	10	20
CAPACITY (kg)	1.1	1.1	2.3	2.3	4.5	4.5	9.1
UL FIRE RATING	1-A:10-B:C	1-A:10-B:C	3-A:40-B:C	3-A:40-B:C	4-A:80-B:C	4-A:80-B:C	20-A:120-B:C
AGENT TYPE	ABC	ABC	ABC	ABC	ABC	ABC	ABC
CYLINDER MATERIAL	Steel	Steel	Steel	Steel	Steel	Steel	Steel
VALVE MATERIAL	Plated Brass	Plated Brass	Plated Brass	Plated Brass	Plated Brass	Plated Brass	Plated Brass
HANDLE/LEVER MATERIAL	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
EXPELLANT	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen	Nitrogen
Operating Pressure @ 70°F	195	195	195	195	195	195	195
TEMPERATURE RANGE (°F)	-40 to 120	-40 to 120	-40 to 120	-40 to 120	-40 to 120	-40 to 120	-40 to 120
TEMPERATURE RANGE (°C)	-40.0 to 48.9	-40.0 to 48.9	-40.0 to 48.9	-40.0 to 48.9	-40.0 to 48.9	-40.0 to 48.9	-40.0 to 48.9
AGENT FLOW RATE (lb./sec)	0.31	0.31	0.39	0.39	0.54	0.51	0.75
AGENT FLOW RATE (kg/sec)	0.14	0.14	0.18	0.18	0.24	0.23	0.34
NOM. DISCHARGE TIME (sec)	9.5	9.5	14	14	22	22	28
DISCHARGE RANGE (ft.)	10.0 to 15.0	10.0 to 15.0	12.0 to 18.0	12.0 to 18.0	16.0 to 20.0	16.0 to 20.0	16.0 to 20.0
DISCHARGE RANGE (m)	3.0 to 4.6	3.0 to 4.6	3.7 to 5.5	3.7 to 5.5	4.9 to 6.1	4.9 to 6.1	4.9 to 6.1
UNIT HEIGHT (in.)	14.87	14.87	15.25	15.25	19.13	18.94	21.13
UNIT HEIGHT (cm)	37.8	37.8	38.7	38.7	48.6	48.1	53.7
UNIT WIDTH (in.)	5.5	5.5	7.25	7.5	8.13	7.75	9.25
UNIT WIDTH (cm)	14.0	14.0	18.4	19.1	20.7	19.7	23.5
UNIT DEPTH (in.)	3	3	4.25	4.25	5.25	5.25	7.25
UNIT DEPTH (cm)	7.6	7.6	10.8	10.8	13.3	13.3	18.4
SHIPPING WEIGHT (lb.)	5.4	5.8	10.4	10.4	18	18	33
SHIPPING WEIGHT (kg)	2.4	2.6	4.7	4.7	8.2	8.2	15.0
USCG APPROVAL	Type B:C Size-I	Type B:C Size-I	Type A Size-II Type B:C Size-I	Type A Size-II Type B:C Size-I	Type A Size-II Type B:C Size-II	Type A Size-II Type B:C Size-II	Type A Size-II Type B:C Size-III
BRACKET	MB-250 Optional	MB-250 Included	MB-5 Included	MB-5 Optional	UB-10 Optional	UB-10 Optional	UB-20 Optional

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Badger Fire Protection for your local distributor for assistance.

Distributed by:

Badger Fire Protection  
944 Glenwood Station Lane, Suite 303  
Charlottesville, VA 22901  
Tel.: 434.964.3200 • Fax: 434.964.3202  
www.badgerfire.com

SS B-001  
All Rights Reserved.

May 2008



A UTC Fire & Security Company