

# Residential Series

## Garage/Workshop Fire Extinguisher (Primary Protection)

Part Number 21005765

Garage/Workshop use

Single use

UL Rated 3-A:40-B:C



Meets NFPA recommendations for the garage and workshop



### Description

Due to the volume of flammable liquids normally present in garages & workshops, a higher rated fire extinguisher is recommended.

Fights fires common to the garage and workshop such as paint, wood, gasoline & energized electrical equipment. This unit is easy to use and has a 10 year warranty.


Features bilingual nameplate and carton

Red finish.

### At a Glance

- Model FX340GW
- Multipurpose Dry Chemical
- UL listed
- UL rated 3-A:40-B:C
- Supplied with wall hanger
- Monoammonium Phosphate
- 10 year limited warranty

For use on the following types of fire:



### Product Specification

Net agent weight (Average)	5.0 lb.
Unit weight (Average)	7.75 lb.
Diameter	4.5 inches
Height	16.07 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Wall hanger	UL Listed

### Features

- Pressure gauge allows for immediate pressure status check
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 5 lb. of fire extinguishing agent (Average)
- 10 year limited warranty
- UL approved wall hanger
- Powder coated cylinder for corrosion protection



UPC: 0-47871-05765-8

### Packaging Options

Master Pack (2)	21005765
Master Pack (4)	21005766
Cut Case (8)	21005767



MASTER PACK



MASTER PACK



CUT CASE