



Commercial Vehicle Fire Protection



Commercial Vehicle Extinguishers

Page 3	Contents
Page 4	Federal Motor Carrier Association Requirements
Page 5	440160 Fire Control FC5 - 5-B:C
Page 6	440161 Fire Control FC10 - 10-B:C
Page 7	440162 Fire Control FC110 - 1-A:10-B:C
Page 8	466422 Fire Control FC10M - 10-B:C
Page 9	466423 Fire Control FC110M - 1-A:10-B:C
Page 10	466425 Fire Control FC340M - 3-A:10-B:C

Fire Control Fire Extinguisher (FC5)

Part number 440160

Regular use

Disposable

UL Rated 5-B:C



For use on the following types of fire:



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Fire Control FC5 unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Supplied with plastic bracket with metal strap.

At a Glance

- Model FC5
- Regular Dry Chemical
- UL listed
- UL rated 5-B:C
- U.S.C.G, DOT approved
- Supplied with retention strap bracket
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on liquid & energized electrical fires

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection



UPC: 0-47871-40160-4

Product Specification

Net agent weight (Average)	2 lb.
Unit weight (Average)	2.85 lb.
Diameter	3.25 inches
Height	10.95 inches
Discharge time	8-12 seconds
Discharge range	4-6 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Fire Control Fire Extinguisher (FC10)

Part number 440161

Regular use

Disposable

UL Rated 10-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Fire Control FC10 unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Supplied with plastic bracket with metal strap.


Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2.9 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection

At a Glance

- Model FC10
- Regular Dry Chemical
- UL listed
- UL rated 10-B:C
- U.S.C.G, DOT approved
- Supplied with retention bracket with metal strap
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on liquid & energized electrical fires

For use on the following types of fire:



UPC: 0-47871-40161-1

Product Specification

Net agent weight (Average)	2.9 lb.
Unit weight (Average)	3.9 lb.
Diameter	3.25 inches
Height	13.75 inches
Discharge time	8-12 seconds
Discharge range	6-8 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Fire Control Fire Extinguisher (FC110)

Part number 440162

Multipurpose use

Disposable

UL Rated 1-A, 10-B:C



For use on the following types of fire:



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The FC 110 unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Supplied with plastic bracket with metal strap.

At a Glance

- Model FC110
- Multipurpose Dry Chemical
- UL listed
- UL rated 1-A, 10-B:C
- U.S.C.G, DOT approved
- Supplied with retention strap bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2.5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection



UPC: 0-47871-40162-8

Product Specification

Net agent weight (Average)	2.5 lb.
Unit weight (Average)	3.9 lb.
Diameter	3.25 inches
Height	13.75 inches
Discharge time	8-12 seconds
Discharge range	6-8 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Fire Control 2.75 R Fire Extinguisher (FC10M)

Part number 466422

Regular use

Rechargeable

UL Rated 10-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Fire Control 2.75 R is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder & sturdy aluminum valve assembly.

Supplied with plastic bracket with metal strap.

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 2.9 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- Powder coated cylinder for corrosion protection

At a Glance

- Model FC10M
- Regular Dry Chemical
- Rechargeable
- UL listed
- UL rated 10-B:C
- U.S.C.G, DOT approved
- Supplied with plastic bracket with metal strap
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



UPC: 0-47871-66422-1

Product Specification

Net agent weight (Average)	2.9 lb.
Unit weight (Average)	4.38 lb.
Diameter	3.25 inches
Height	14.4 inches
Discharge time	8-12 seconds
Discharge range	8-12 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Fire Control 2.5 MP Fire Extinguisher (FC110M)

Part number 466423

Multipurpose use

Rechargeable

UL Rated 1-A, 10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The PRO 2.5MP is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder & sturdy aluminum valve assembly.

Supplied with plastic bracket with metal strap.
All metal retention bracket.
Pt # 46642301
All metal double strap bracket: Pt # 46642333



At a Glance

- Model FC110M
- Multipurpose Dry Chemical
- Rechargeable
- UL listed
- UL rated 1-A, 10-B:C
- U.S.C.G, DOT approved
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 2.6 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- Powder coated cylinder for corrosion protection

For use on the following types of fire:



UPC: 0-47871-66423-8

Product Specification

Net agent weight (Average)	2.6 lb.
Unit weight (Average)	3.9 lb.
Diameter	3.25 inches
Height	15.0 inches
Discharge time	8-12 seconds
Discharge range	10-15 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Fire Control Fire Extinguisher (FC340M-VB)

Part number 466425

Multipurpose use

Rechargeable

UL Rated 3-A, 40-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The FC340M-VB unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough metal valve assembly.

Supplied with metal retention bracket.


Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- Powder coated cylinder for corrosion protection

At a Glance

- Model FC340M-VB
- Multipurpose Dry Chemical
- UL listed
- UL rated 3-A, 40-B:C
- Supplied with retention bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



UPC: 0-47871-66425-2

Product Specification

Net agent weight (Average)	5.0 lb.
Unit weight (Average)	7.9 lb.
Diameter	4.5 inches
Height	16.07 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK