



Accordion Wheel Conveyor



Accordion Roller Conveyor

Accordion Conveyors

MEDIUM/HEAVY DUTY ACCORDION WHEEL CONVEYORS:

Flexible conveyors conform to the various shapes necessary for ease of product handling with lengths available up to 60 feet.

MEDIUM/HEAVY DUTY ACCORDION ROLLER CONVEYORS:


Flexible conveyors designed for packages with flat or irregular bottoms.

IMPACT CONVEYORS (FIXED): Aluminum channel rigid frame with steel wheels is bolted to the receiving end of the conveyor. Skate wheels on 3" axle centers withstand impact of heavy materials.

SWING STICK: 5' rigid frame aluminum Swing Stick with 3" axle centers attaches to end of conveyor and extends up into truck beds. When not in use, it nests on top of conveyor.



Impact Conveyor



Swing Stick

MEDIUM DUTY ACCORDION WHEEL SPECIFICATIONS:

Load Capacity: 226 lbs. per lineal ft. when fully extended ♦ Standard Height Adjustment: 28" - 44" ♦ 1 Box Stop and 1 Set of Hook Couplers per unit ♦ Casters: 5" x 1-1/2" swivel with foot brake.

HEAVY DUTY ACCORDION WHEEL SPECIFICATIONS:

Load Capacity: 275 lbs. per lineal ft. when fully extended ♦ Double Cross Braces and Double Wall Inner Leg Supports ♦ 7 gauge side links with black epoxy finish ♦ Standard Height Adjustment: 28" - 36"

MEDIUM DUTY ACCORDION ROLLER SPECIFICATIONS:

Load Capacity: 200 lbs. per lineal ft. ♦ 1-3/8" O.D. Galvanized Steel Rollers on 5-1/4" Axle Centers ♦ 28" to 36" ♦ Box Stop, Pull Handle & Couplers Standard ♦ 5 x 1-1/2" Swivel/Wheel Lock Casters

► MEDIUM DUTY ACCORDION ROLLER CONVEYORS

LENGTH ADJUSTMENT WITH 5 1/4" AXLE CENTERS			18" WIDTHS		24" WIDTHS	
Length Contracted/Extended at Maximum	Leg Sets Per Unit	Bed Sections Per Unit	Model No	Rollers Per Section	Model No	Rollers Per Section
2' 7" - 8' 6"	3	2	RLR18008S	9	RLR24008S	9
3' 9" - 12' 2"	4	3	RLR18012S	9	RLR24012S	9
4' 10" - 15' 10"	5	4	RLR18016S	9	RLR24016S	9
5' 11" - 19' 6"	6	5	RLR18020S	9	RLR24020S	9
7' 0" - 23' 2"	7	6	RLR18024S	9	RLR24024S	9
8' 4" - 27' 9"	8	7	RLR18028S	9	RLR24028S	9
9' 5" - 31' 5"	9	8	RLR18032S	9	RLR24032S	9
10' 6" - 35' 1"	10	9	RLR18036S	9	RLR24036S	9
12' 5" - 41' 6"	12	11	RLR18040S	9	RLR24040S	9