

A sunset over the ocean with a large, bright sun low on the horizon. The sky is a mix of orange, yellow, and purple. In the foreground, the silhouettes of several sailboats are visible against the water.

Marine Fire Protection

Marine 210D MPWC Fire Extinguisher

Part number 466636

Regular use

Disposable

UL Rated 5-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The PWC unit is fitted with a "one touch" pressure check device to ensure reliable performance. It is manufactured from lightweight aluminum and a tough nylon valve assembly.

Features bilingual nameplate and carton.

Features

- Pressure check device to determine fire extinguisher's readiness status
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety clip
- Rust and impact resistant nylon handle
- 2.0 lb of fire extinguishing agent (Average)
- 2 year limited warranty
- UL approved bracket
- Powder coated cylinder for corrosion protection



At a Glance

- Model MPWC
- Regular Dry Chemical
- UL listed
- UL rated 5-B:C
- Sodium Bicarbonate
- 2 year limited warranty
- Suitable for use on liquid & energized electrical fires

For use on the following types of fire:



UPC: 0-47871-66636-2

Product Specification

Net agent weight (Average)	2.0 lb
Unit weight (Average)	3.1 lb
Diameter	2.9 inches
Height	12.75 inches
Discharge time	8-10 seconds
Discharge range	10-14 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Mariner 10 Fire Extinguisher

Part number 466628

Regular use

Disposable

UL Rated 10-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).


The Mariner 10 unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Features bilingual nameplate and carton.

At a Glance

- Model Mariner 10
- Regular Dry Chemical
- UL listed
- UL rated 10-B:C
- U.S.C.G, DOT approved
- Supplied with retention strap bracket
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on liquid & energized electrical fires

For use on the following types of fire:



Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2.9 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection



UPC: 0-47871-66628-7

Product Specification

Net agent weight (Average)	2.9 lb
Unit weight (Average)	3.9 lb
Diameter	3.25 inches
Height	13.75 inches
Discharge time	8-12 seconds
Discharge range	6-8 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Mariner 110 Fire Extinguisher

Part number 466627

Multipurpose use

Disposable

UL Rated 1-A, 10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Mariner 110 unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Features bilingual nameplate and carton.

At a Glance

- Model Mariner 110
- Multipurpose Dry Chemical
- UL listed
- UL rated 1-A, 10-B:C
- U.S.C.G, DOT approved
- Supplied with retention strap bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2.5 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection



UPC: 0-47871-66627-0

Product Specification

Net agent weight (Average)	2.5 lb
Unit weight (Average)	3.9 lb
Diameter	3.25 inches
Height	13.75 inches
Discharge time	8-12 seconds
Discharge range	6-8 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Mariner 5 Fire Extinguisher

Part number 466635

Regular use

Disposable

UL Rated 5-B:C



Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Kitchen/Garage unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Features bilingual nameplate and carton.

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection

At a Glance

- Model Mariner 5
- Regular Dry Chemical
- UL listed
- UL rated 5-B:C
- U.S.C.G, DOT approved
- Supplied with retention strap bracket
- Sodium Bicarbonate
- 6 year limited warranty
- Suitable for use on liquid & energized electrical fires

For use on the following types of fire:



UPC: 0-47871-66635-5

Product Specification

Net agent weight (Average)	2 lb
Unit weight (Average)	2.85 lb
Diameter	3.25 inches
Height	10.95 inches
Discharge time	8-12 seconds
Discharge range	4-6 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK

Mariner 340 Fire Extinguisher

Part number 468089

Multipurpose use

Rechargeable

UL Rated 3-A, 40-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Mariner 340 unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough metal valve assembly.

Features bilingual nameplate and carton.

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with supplied metal mounting bracket
- Powder coated cylinder for corrosion protection
- Supplied with U.S.C.G. approved bracket

At a Glance

- Model Mariner 340
- Multipurpose Dry Chemical
- UL listed
- UL rated 3-A, 40-B:C
- Supplied with metal strap bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



Product Specification

Net agent weight (Average)	5.0 lb
Unit weight (Average)	9.0 lb
Diameter	4.5 inches
Height	16.07 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options



UPC: 0-47871-68089-4



MASTER PACK