Mariner 340 Fire Extinguisher

Part number 468089 Multipurpose use

•

• 0 •

•

.

•

.

•

•

•

•

•

•

•

•

•

• .

.

• .

• • . •

• •

0

.

•

.

•

.

• . . . • .

. 0 • .

• 0 • • .

•

•

Rechargeable

UL Rated 3-A, 40-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Mariner 340 unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough metal valve assembly.

Features bilingual nameplate and carton.

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5 lb of fire extinguishing agent (Average)
- 6 year limited warranty UL approved wall hanger
- Coast Guard (U.S.C.G) approved when fitted with supplied metal mounting bracket
- Powder coated cylinder for corrosion protection
- Supplied with U.S.C.G. approved bracket



UPC: 0-47871-68089-4

At a Glance

- Model Mariner 340
- Multipurpose Dry Chemical
- **UL** listed
- UL rated 3-A, 40-B:C
- Supplied with metal strap bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following

types of fire:

Product Specification	
Net agent weight (Average)	5.0 lb
Unit weight (Average)	9.0 lb
Diameter	4.5 inches
Height	16.07 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Packaging Options





•

