

Today's North American workers are getting physically bigger and the old ideas of maximum worker weight have become outdated. North Heavy Duty Harnesses are designed to go beyond the performance requirements of North American standards to provide safe and reliable fall protection for workers above 310lbs.

Rated for a full 440lbs, these harnesses meet the needs of the larger worker, or those whose tooling and equipment carrying needs place them over the traditional limits of existing standards.



HEAVY DUTY HARNESS

Features/Benefits

- Rated for 440lbs Exceeds the requirements of CSA and ANSI to provide reliable fall protection for workers above the CSA/ANSI limit of 310lbs (total weight of person plus tools and equipment).
- Back and side D-rings For fall arrest and work positioning applications (CSA class AP).
- FP80K/3DYQ320 features an integrated back and shoulder pad – Conforms to the wearers shape to provide all-day comfort.
- Integrated 440lbs rated, Soft-Pak lanyard Permanently attached lanyard ensures that both lanyard and harness are correctly rated to 440lbs.
- Adjustable lanyard Integrated lanyard is adjustable from 4ft to 6ft in length (FP80H only).
- Tongue and buckle leg straps Provide faster and easier donning and adjustment.
- Universal size with full adjustability One size fits most





Part No					Shoulder Strap Adjustment		
	LARGE W/ SHOCK ABSORBER	YES	NO	NO	QC	TONGUE	QC

Accessories for FP80K ONLY



FP21122/6

Part No	Material	Туре	Body Connector	Anchorage Connector	Lengths Available
FP21122/	NYLON ROPE	RESTRAINT	SNAP HOOK	SNAP HOOK	4,5,6
FP21129/	NYLON ROPE	RESTRAINT	SNAP HOOK	REBAR/LADDER HOOK	4,5,6
FP255222/	NYLON 1"	Y-LANAYRD RESTRAINT	SNAP HOOK	SNAP HOOK	4,5,6
FP2552GG/	NYLON 1"	Y-LANAYRD RESTRAINT	SNAP HOOK	SCAFFOLD HOOK	4,5,6



