

Fire Control 2.5 MP Fire Extinguisher (FC110M)

Part number 466423

Multipurpose use

Rechargeable

UL Rated 1-A, 10-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The PRO 2.5MP is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder & sturdy aluminum valve assembly.

Supplied with plastic bracket with metal strap.
All metal retention bracket.
Pt # 46642301
All metal double strap bracket: Pt # 46642333


At a Glance

- Model FC110M
- Multipurpose Dry Chemical
- Rechargeable
- UL listed
- UL rated 1-A, 10-B:C
- U.S.C.G, DOT approved
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 2.6 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- Powder coated cylinder for corrosion protection

For use on the following types of fire:



UPC: 0-47871-66423-8

Product Specification

Net agent weight (Average)	2.6 lb.
Unit weight (Average)	3.9 lb.
Diameter	3.25 inches
Height	15.0 inches
Discharge time	8-12 seconds
Discharge range	10-15 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

Packaging Options



MASTER PACK