

# 34 HP Briggs & Stratton Vanguard-Diesel

Also available in 33 hp Kubota



2-1/2AGE 34BS

- ▶ Dependable Briggs & Stratton Vanguard diesel engine
- ▶ 2-year engine, 3-year pump,
- ▶ Stainless steel shaft and bronze impeller

**Features:** 4 cycle, 3 cylinder, 34 HP Turbo Briggs & Stratton Vanguard diesel engine, with electric start, recoil rope back-up, 6-gallon fuel tank, hose and adapter.

**Options:** Dual remote controlled panels, adapters and caps, electric primer, spark arrest muffler. Other options available.

Model	Uses	Performance	Inlet	Outlet	Dimensions	Weight	Price
<b>1-1/2AGE 34BS (Liquid-Cooled)</b>	Pressure	180 gpm @ 130 psi 130 gpm @ 200 psi 80 gpm @ 275 psi	2" NPT	2-1 1/2" NPT	Length: 38" Width: 25" Height: 28"	370 lbs. (168 kg)	\$12,700.00
<b>2-1/2AGE 34BS (Liquid-Cooled)</b>	Pressure Volume	300 gpm @ 85 psi 200 gpm @ 135 psi 50 gpm @ 215 psi	2 1/2" NPT	2-1 1/2" NPT and 1-2 1/2" NPT	Length: 40" Width: 28" Height: 28"	380 lbs. (173 kg)	\$12,800.00
<b>HE 34BS (Liquid-Cooled)</b>	Volume	500 gpm @ 30 psi 300 gpm @ 100 psi 100 gpm @ 153 psi	Assembly #1 - 4" NPT Assembly #2 - 4" NH Assembly #3 - 4" NH	3" NPT 1-2 1/2" & 2-1 1/2" NPT 2-2 1/2" NH	Length: 37" Width: 20" Height: 31"	490 lbs. (222 kg)	Assembly #1 - \$12,900.00 Assembly #2 - \$13,200.00 Assembly #3 - \$13,800.00

## HE34BSD

**NEW**

Many of our customers have been asking for a multipurpose pump that can be used for everything from filling tankers, initial attack, to brush fires. The new HE34BSD has been the answer for quite a few of them and is now available as a crossmount package. Powered by the new, popular Briggs & Stratton 34 hp diesel engine, this water-cooled engine features electric start and a compact design.

### Dimensions

- ▶ 37" L x 20" W x 31" H

### Performance

500 gpm @ 30 psi  
300 gpm @ 100 psi  
100 gpm @ 153 psi

### Assembly #1:

- ▶ Aluminum alloy casing
- ▶ Bronze impeller and seal ring
- ▶ 4" NPT suction
- ▶ 3" NPT discharge

### Assembly #2:

- ▶ 4" NH suction and screen
- ▶ 1-2 1/2" and 2-1 1/2" NPT discharge head with check valve

### Assembly #3:

- ▶ 4" NH suction and screen
- ▶ 2-2 1/2" NH discharges, 1/4 turn, ball, self-locking, all bronze valves

### Assembly #4:

- ▶ Cross mount (call for pricing)

