Dry Chemical





Heavy-duty fire protection equipment

High capacity wheeled fire extinguisher models designed for single person operation and to pass through 36-inch wide industrial doorways. Badger pressure transfer wheeled extinguishers are ideal for use in rugged industrial applications or anywhere the need for quick and simple on-site equipment recharge capability is desired.

The "Multipurpose" agent models are suitable for use on Class A,B and C fires. The "Regular" and "Purple K" agent models are suitable for Class B and C fires.

Features:

- Heavy-duty cylinder activation valves
- · Equipped with 50' hose length
- · Heavy-duty steel frames
- UL Listed and USCG Approved—Meets D.O.T. requirements
- 12 year periodic hydrostatic test interval
- Six year warranty

Regular BC and Purple K Dry Chemical:









ABC Multipurpose Dry Chemical:













Technical Data:

BADGER Wheeled Dry Chemical Pressure Transfer Models

MODEL	WB491	WB493
PART NUMBER	24126	24129
CAPACITY (lb.)	300	300
CAPACITY (kg)	136	136
UL FIRE RATING	40-A:320-B:C	320-B:C
AGENT TYPE	ABC	Purple K
CYLINDER MATERIAL	Steel	Steel
VALVE MATERIAL	Brass	Brass
HANDLE/LEVER MATERIAL	n/a	n/a
EXPELLANT	55 cu.ft.N2	55 cu.ft.N2
Operating Pressure @ 70° F	240	240
TEMPERATURE RANGE (° F)	-65 to 120	-65 to 120
TEMPERATURE RANGE (° C)	-54.0 to 48.9	-54.0 to 48.9
AGENT FLOW RATE (lb/sec)	4.9	4.1
AGENT FLOW RATE (kg/sec)	2.2	1.86
NOM. DISCHARGE TIME (sec)	60	67
DISCHARGE RANGE (ft.)	30 to 40	30 to 40
DISCHARGE RANGE (m)	9.1 to 12.2	9.1 to 12.2
UNIT HEIGHT (in.)	57	57
UNIT HEIGHT (cm)	145	145
UNIT WIDTH (in.)	34	34
UNIT WIDTH (cm)	86.4	86.4
UNIT DEPTH (in.)	39	39
UNIT DEPTH (cm)	99	99
SHIPPING WEIGHT (lb.)	743	743
SHIPPING WEIGHT (kg)	337	337
USCG APPROVAL	yes	yes

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Badger Fire Protection for your local distributor for assistance.

Distributed by:





