

BallyLifts One Person Maintenance Lift

Bally Lifts One person maintenance lifts

One worker lift with 300 lbs. rated capacity

- **Totally enclosed platform with 42" guardrails, midrails, and gate; 4" toeboards and skid resistant mat**
- **Two platform styles available:**
 - Standard platform with steel deck (BL-315)
 - Cantilevered platform with aluminum deck (BL-C14)
- **Built-in ladder with flat, skid resistant treads and grab rails provides access to platform in fully lowered position while anti-skid rungs provide access to platform when lift is raised**
- **Compact base frame rolls on two swivel and two rigid 6" casters**
- **Rails fold down for doorway passage and easy storage**
- **Base is 32" wide by 65" long, outriggers extend to 68" wide**
- **Leveling jacks secure lift to the floor**
- **Hydraulic hand pump provides easy lifting**
- **Standard finish is deep gray enamel paint**
- **Meets/ exceeds ANSI safety standards**



[ENLARGE IMAGE](#)



Rolls thru standard doorway



Cantilevered Model BL-C14
One worker / 300 lbs. capacity

	Model Number	Platform Max	Platform Min	Platform Length	Platform Width	Weight Lbs.
Standard	BL-315	15'	6' 4"	20"	28"	590
Cantilevered	BL-C14	14'	6' 4"	64"	20"	900

OPTIONAL ACCESSORIES

AC electric power
DC electric power

- Minimum storage height of 78"
- BL-315 ships at

Three available power options:

- Convenient plug in 120V AC
- Independent 12V DC deep cycle system complete with battery and charger
- Air hydraulic power requiring 90 CFM with 90 PSI pressure