

Rope grab/lifeline combinations still provide some of the most cost-effective solutions for fall protection needs. North offers you the widest assortment of rope implements in the market ranging from automatic rope grabs to rope adjusters. All are constructed from quality, corrosion resistant materials for long service life. Match the device with the lifeline product that most suits your needs. All automatic rope grabs are engineered to meet or exceed applicable ANSI, OSHA and CSA requirements.

AUTOMATIC ROPE GRAB WITH PARK FEATURE





FP561

Features/Benefits

- FP562 Should be used for sternal connection only
- Rope grabs trail user without manipulation
- Bolt-action, quick closure system
- FP560 series rope grab are compatible with 3/4" rope

Part No	Description	Rope Type
FP561	Automatic rope grab with parking feature	16E & 16ST
FP562	FP561 with 6" (150 mm) web lanyard with carabiner	16E & 16ST
FP563	FP561 with 2' (0.6 m) web lanyard with snap hook	16E & 16ST
FP564	FP561 with 2' (0.6 m) Soft Pak energy absorbing lanyard with snap hook	16E & 16ST
FP582	FP561 with 6" (150 mm) soft pak energy absorbing lanyard with snap hook for 1/2" (13 mm) rope	13ST

AUTOMATIC ROPE GRAB





Features/Benefits

- Rope grab will trail user without manipulation
- Rope grab will stop on a lifeline even when the panic lock is held open

Part No	Description	Rope Type
FP541	Automatic panic lock rope grab	16E & 16ST
FP542	FP541 with 2' (0.6 m) Lanyard energy absorber with snap hook	16E & 16ST
FP543	FP541 with 2' (0.6 m) lanyard	16E & 16ST

MANUAL ROPE ADJUSTERS



Features/Benefits

- FP550 Series Rope Grabs are not CSA approved for fall arrest. Can be used for travel restraint applications in Canada only
- Rope grab requires manual assistance for travel in at least one direction
- Meets or exceeds ANSI and OSHA requirements

Part No	Description	Rope Type
FP551	Manual rope grab	16E & 16ST
FP552	FP551 with 2' (0.6 m) lanyard energy absorber with snap hook	16E & 16ST

North provides a wide variety of lifelines to choose from. From economical 3-strand rope to premium, low stretch kernmantle ropes there is a lifeline for every vertical application.

Part No	Description	Composition	Tensile Strength	Floats Length
FP16E/SP/	5/8" (16mm) 3-strand	Polyolefin fiber	8,100lbs (3680kgs)/36.00kN	Yes 25,50,100
FP16E/PS/	5/8" (16 mm) 3-strand	Co-polymer blend	10,00lbs (4540kgs)/44.44kN	Yes 25,50,100
FP16ST/KL/	5/8" (16mm) Kernmantle	Nylon	12,570lbs (5700kgs)/55.87kN	No 25,50,100
FP16ST/KH/	5/8" (16mm) Kernmantle	Polyester	14,775lbs (6700kgs)/65.58kN	No 25,50,60,100

ROPE ADJUSTERS	
NOLE WANTARIERS	

FP16E/SP/

VERTICAL LIFELINES







Part No	Description	Rope Type
FP3571	Rope adjuster with eye	16E & 16ST
FP3521	Rope tensioner	16ST