

NEW

# Portable Pumps

## Ohler Pumps

### Features

- ▶ Fuel transfer with electric start
- ▶ Potable water transfer
- ▶ Water transfer
- ▶ Pump case, inlet flange, volute, impeller, and wear plate are sand cast aluminum and heat-treated
- ▶ Anodized aluminum quick couplings
- ▶ Shaft extension and metal seal components constructed of stainless steel
- ▶ Self lubricating mechanical shaft seal
- ▶ Air-cooled, single cylinder, 4-stroke diesel engine
- ▶ 6.1 horsepower (continuous) at 3,600 rpm
- ▶ Fuel capacity of 2.5 hours of operation at rated load



150AAMCFP-1B30CS

Model	NSN	Description	Price
150AAMCFP-1B30CS	4320-01-547-8729	150 gpm Fuel Transfer Pump w/Electric Start Option (Portable)	\$7,330.00
150AAMCWP-1B30	4320-01-547-8734	150 gpm Potable Water Transfer Pump (Portable)	\$6,090.00
RA1029	4320-01-259-4407	125 gpm Water Transfer Pump (Portable)	\$6,940.00
RA1013	4320-01-390-8214	125 gpm Fuel Transfer Pump (Portable)	\$6,970.00
AFPS-6315-24VDC	4320-01-247-2633	DC Motor-Driven Fuel Transfer Pump w/Accessories Package	\$4,420.00

## 13 BS Floating Pump

- ▶ Dependable Briggs & Stratton engine
- ▶ New float design for easier carrying and greater stability
- ▶ Take advantage of swimming pools, reservoirs, ponds, etc.

**Features:** 13 HP I/C Briggs & Stratton, single-cylinder, 4-cycle, air cooled, recoil rope start. Fuel is regular unleaded gas with no mixing of oil required. 2-quart fuel tank.

**Float:** High-density polyethylene filled with closed-cell polyurethane foam. Four built-in carrying handles.



Model	Uses	Performance	Inlet	Outlet	Dimensions	Weight	Price
13 BS Floating Pump	Volume	405 gpm @ 15 psi 250 gpm @ 40 psi 200 gpm @ 45 psi 100 gpm @ 60 psi	----	2 1/2" NH	Length: 33" Width: 30" Height: 20"	120 lbs. (54 kg)	\$2,710.00

## 13 HP Vanguard

Also available in 10 hp Briggs & Stratton or 13 hp Honda

- ▶ 2-year engine warranty, 3-year pump
- ▶ Can easily be carried by two firefighters

**Features:** 13 HP Briggs & Stratton Vanguard Engine with 8.8 qt. fuel tank, electric start with recoil rope back-up, exhaust primer, bronze impeller and wear rings, stainless steel shaft, discharge head with check valve and base with carrying handles.

**Options:** Gauge, adapters and caps. Other options available.



1-1/4AGE 13V

Model	Uses	Performance	Inlet	Outlet	Dimensions	Weight	Price
1-1/4AGE 13V	Pressure	60 gpm @ 170 psi 40 gpm @ 230 psi 20 gpm @ 275 psi	1 1/2" NPTF	2-1 1/2" NPTF	Length: 26" Width: 21" Height: 20"	141 lbs. (64 kg)	\$4,470.00
1-1/2AGE 13V	Pressure	120 gpm @ 80 psi 75 gpm @ 130 psi 25 gpm @ 155 psi	2" NPT	2-1 1/2" NPT	Length: 26" Width: 21" Height: 20"	141 lbs. (64 kg)	\$4,460.00
2BE 13V	General Purpose	300 gpm @ 15 psi 150 gpm @ 70 psi 80 gpm @ 100 psi	3" NPTF	1-2 1/2" NPTF	Length: 26" Width: 21" Height: 20"	141 lbs. (64 kg)	\$4,230.00
HE 13V	Volume	390 gpm @ 20 psi 200 gpm @ 55 psi 50 gpm @ 65 psi	4" NPTF	1-2 1/2" NST 2-2 1/2" NST	Length: 26" Width: 21" Height: 20"	167 lbs. (76 kg)	\$4,820.00