


LOCKOUT


GATE VALVE LOCKOUT



Application of the Safetee Donut® and a secure padlock assures that the valve remains in the OFF or ON position.

Catalog #	Size
	Fits valve handle diameter
GV-01	1" - 2 1/2"
GV-02	2 1/2" - 5"
GV-03	5" - 6 1/2"
GV-04	6 1/2" - 10"
GV-05	10" - 13"

BALL VALVE LOCKOUT



Catalog #	Fits
BV-07A	3/8" - 2 1/2" valves
BV-03	2"-8" valves

The Ball Valve Lockout is designed to fit all major brand one quarter turn ball valves. Its easy-to-use design requires no special padlocks. Made of tough and durable polypropylene material.

BV-07A locks out valves on pipes from 0.50" to 1.25" diameter in the "ON" position (handle parallel to pipe) and up to 2.5" in diameter pipes in the "OFF" position. (handle perpendicular to pipe.) **BV-03** locks out valves in the "OFF" position only.

BREAKER LOCKOUTS



Catalog #	Style
BL01	Single Pole
BL03	Multi Pole

Model BL01 fits most major brand single pole breakers.

Catalog #	Size
NHLO	Fits toggles up to 1/2" wide.

This "NO-HOLE" Lockout is designed to fit breaker toggles up to 1/2" wide without the toggle hole required with the Lockouts. It installs with a set screw for anchoring.

PLUG LOCKOUT



Catalog #	Size
PLO-S	1/2" dia. cord, 110 VAC (2" x 2" x 3 1/2")

Hinged halves close over plug and lock with a padlock for prevention of accidental reconnection. Use on specific sizes.

ENGLISH / BILINGUAL PLUG LOCKOUT

Made of bright yellow thermoplastic, these devices give a visual warning and will fit any size plug. English or Bilingual available.



Cat. #	Size
UPLO	Accommodates plugs up to 3" in diam. and 5 1/2" long, with a maximum cord diameter of 1 1/4".
UPLO-B	Same as above, bilingual.

WALL SWITCH LOCKOUT



WSLO

Clear plastic device uses existing wall plate screws to mount. When locked closed this device prevents inadvertent switch access.

AC SENSOR



ACS

This instrument is a non-contact AC voltage sensor that can be used to detect the presence or the absence of AC voltage in order to prevent electrical shock. It detects 50-1000 volts. The user simply places the sensor on the test area. If voltage is present - tip glows cherry red. Sensor is a UL listed instrument that is manufactured 100% in the USA.

UNIVERSAL CIRCUIT BREAKER LOCKOUT

NEW



UCBL

Our handy Universal Circuit Breaker Lockout eliminates the need to maintain numerous lockouts. This versatile piece fits any electrical circuit breaker with switches .3" to .6" x .25" to .46" thick. Easily mounts using only a standard screwdriver. Danger label provides workers with an added level of alert. Accommodates up to 2 padlocks (sold separately on facing page).

SAFETY LOCKOUTS



LSO-1
1" I.D. interlocking tab diameters

LSO-1 1/2
1 1/2" interlocking tab diameters

Multiple lockout made of polyester-coated aluminum will hold up to 6 padlocks. 2 sizes available.

Locks sold separately on facing page.



LSO-D
1" I.D. & 1 3/4" I.D.
Polyester-coated steel dual-multiple lockout. Holds up to 6 padlocks.



LSO-U
1" wide x 2" long
Universal lockout made of tough, durable nylon. Colored bright orange for clear visibility. Entire lockout measures 7" long and weighs only 1 oz. Conveniently hangs on tool belt. Non-conductive, dielectric.