## **Compressed Air Foam Systems**

PUMPS

Colt

Mini pumper

Rescues

Wildland/Interface

**Features:** 29HP Kawasaki engine, liquid cooled, V-twin, gasoline powered, fuel injected, vernier throttle, 12-volt electric start, Darley model 1 1/2 AE pump, 1 - fully adjustable 1<sup>1</sup>/<sub>2</sub>" CAF discharge mix point, 1<sup>1</sup>/<sub>2</sub>" water discharge, 2" NPT suction inlet, 2<sup>1</sup>/<sub>2</sub>" water and air pressure gauges, stainless steel plumbing, 12-volt primer. **Options:** Diesel driven version available (Mustang). Call for details.



	Performance						
Model	Water	Air Compressor	Inlet	Outlet	Dimensions	Weight	Price
Colt	100 gpm @ 125 psi	50 cfm @ 125 psi	2 <sup>1</sup> / <sub>2</sub> " NH	1 <sup>1</sup> / <sub>2</sub> " Water	Length: 38"	850 lbs.	Call for
				Discharge	Width: 48"	(386 kg)	Pricing
					Height: 32"	_	877-634-6223

## Derringer

Mini Pumper
Rescues

Wildland/Interface

Simultaneous Flow (NFPA) 110 gpm & 55 cfm @ 125 psi

Simultaneous Flow 130 gpm & 60 cfm @ 100 psi

**Features:** 34 HP Briggs & Stratton Vanguard engine, diesel, liquid cooled, 3 cylinder, 12-volt electric start, turbo charged, Darley model 1 1/2 AGE pump, 2 - independent  $1^{1}/_{2}$ " CAF discharge mix points, 1 - 2" tank to pump suction inlet, 1 - direct tank fill with  $2^{1}/_{2}$ " female swivel, 12-volt electric primer system.



	Perfor	mance			
Model	Water	Air Compressor	Dimensions	Weight	Price
Derringer	130 gpm @ 100 psi	60 cfm @ 125 psi	Length: 48"	1,330 lbs. (603 kg)	Call for
			Width: 48"	Ship. wt. for	Pricing
			Height: 37"	base unit only	877-634-6223

## Kodiak

- 250 gpm, NFPA 1901 rated rear mounted CAFS module
- Mini pumper
- Wildland/Quick attack vehicle

**Features:** 81 HP Detroit diesel engine, liquid cooled, 4 cylinder, turbocharged, diesel fueled, 12-volt electric start with oil pressure gauge, voltmeter, tachometer/hourmeter, vernier throttle, Darley model 2 1/2 AGE pump, 3 - independent  $1^{1}/_{2}$ " CAF discharge mix points, 1 -  $2^{1}/_{2}$ " water discharge, 1 -  $2^{1}/_{2}$ " tank-to-pump suction inlet, master drain valve, Pro-S governor, direct tank fill, 12-volt rotary primer.

> Simultaneous Flow (NFPA) 250 gpm & 125 cfm @ 125 psi



Performance Model Water Air Compressor Inlet Outlet Dimensions Weight Price Kodiak 250 gpm @ 150 psi 130 cfm @ 125 psi 1-21/2" 1-2<sup>1</sup>/<sub>2</sub>" Length: 591/2" 1,880 lbs. Call for 175 gpm @ 200 psi Width: 471/2" (853 kg) Pricing 125 gpm @ 250 psi Height: 46" 877-634-6223