Mariner 10 Fire Extinguisher

Part number 466628 Regular use

.

• .

> • . . •

> •

> .

.

.

•

.

•

.

•

.

.

•

.

•

•

. .

•

• •

.

.

.

. • . • .

• .

.

•

. .

۲

.

•

.

.

.

.

• .

• . . .

Disposable

UL Rated 10-B:C

Description

Suitable for use on Class B (liquids & gases) and Class C fires (energized electrical equipment).

The Mariner 10 unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Features bilingual nameplate and carton.

At a Glance

- Model Mariner 10 •
- Regular Dry Chemical •
 - UL listed

•

G · ELECTRICAL EQUIPMENT

- UL rated 10-B:C
- U.S.C.G, DOT approved
- Supplied with retention strap bracket
- Sodium Bicarbonate .
- 6 year limited warranty •
- Suitable for use on liquid & • energized electrical fires

Features

- Easy-to-read gauge tells you • fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2.9 lb of fire extinguishing agent (Average)
- 6 year limited warranty
- UL approved strap retention bracket
- Coast Guard (U.S.C.G) approved when fitted with supplied mounting bracket
- Powder coated cylinder for corrosion protection



UPC: 0-47871-66628-7

Packaging Options







For use on the following types of fire: **Product Specification**

В + LIQUIDS

Net agent weight (Average)	2.9 lb
Unit weight (Average)	3.9 lb
Diameter	3.25 inches
Height	13.75 inches
Discharge time	8-12 seconds
Discharge range	6-8 feet
Operating pressure	100 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	U.S.C.G approved

Kidde Residential and Commercial Division

1394 South Third Street, Mebane, NC 27302 • Tel. 919.563.2711 • www.kiddeus.com

- • . . .
- . ۲ . • • .

.

•