
Pro SeriesPro 210 Fire Extinguisher (For Low Hazard Protection)Part Number 21005779Multipurpose useRechargeable

UL Rated 2-A:10-B:C



For use on the following types of fire:



Product Specification

Net agent weight (Average) 4 lb. Unit weight (Average) 7.5 lb. Diameter 4.5 inches 15.7 inches Height **Discharge time** 13-15 seconds **Discharge** range 10-15 feet **Operating pressure** 100 psi Cylinder Seamless aluminum Valve/handle/lever Brass/metal/metal Strap Bracket (not supplied) U.S.C.G approved

Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C (energized electrical equipment) fires.

The PRO 210 is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder with a chrome plated brass valve assembly.

For protecting LOW hazard occupancies such as: Offices, churches, assembly halls, classrooms & hotel guest areas.

At a Glance

- Model PRO 210
- Multipurpose Dry Chemical
- Rechargeable
- UL listed
- UL rated 2-A:10-B:C
- U.S.C.G. & DOT approved
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

Features

- Multipurpose Fire Extinguisher
- Aluminum cylinder
- Heavy duty chrome plated brass valve assembly
- Pressure gauge allows for immediate pressure status check
- Rechargeable
- 6 year warranty
- UL rated 2-A, 10-B:C
- UL approved wall hanger
- Coast Guard (U.S.C.G.) approved when fitted with optional mounting bracket
- Optional metal strap bracket Pt # 466400
- Powder coated cylinder for corrosion protection



UPC: 0-47871-05779-5
Packaging Options

Master Pack (4) 21005779

