

Pro Series

Pro 340 Fire Extinguisher (For Moderate Hazard Protection)

Part Number 21005782

Multipurpose use

Rechargeable

UL Rated 3-A:40-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C (energized electrical equipment) fires.

The PRO 340 is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder with a chrome plated brass valve assembly.

For protecting MODERATE hazard occupancies such as: Light manufacturing, dining areas, auto showrooms, parking garages & storage areas.

At a Glance

- Model PRO 340
- Multipurpose Dry Chemical
- Rechargeable
- UL listed
- UL rated 3-A:40-B:C
- U.S.C.G. & DOT approved
- Supplied with wall hanger
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

For use on the following types of fire:



Product Specification

Net agent weight (Average)	5 lb.
Unit weight (Average)	8.5 lb.
Diameter	4.5 inches
Height	15.7 inches
Discharge time	13-15 seconds
Discharge range	10-15 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve/handle/lever	Brass/metal/metal
Strap Bracket (not supplied)	U.S.C.G approved

Features

- Multipurpose Fire Extinguisher
- Aluminum cylinder
- Heavy duty chrome plated brass valve assembly
- Pressure gauge allows for immediate pressure status check
- Rechargeable
- 6 year warranty
- UL rated 3-A, 40-B:C
- UL approved wall hanger
- Coast Guard (U.S.C.G.) approved when fitted with optional mounting bracket
- Powder coated cylinder for corrosion protection
- Optional metal strap bracket Pt # 466400



UPC: 0-47871-05782-2

Packaging Options

Master Pack (4) 21005779



MASTER PACK