

Spray Foam Extinguisher

Part number 466620

A and B capability

Rechargeable

UL Classified
EN3 fire rating 8A, 70B



Description

Suitable for use on Class A (trash, wood & paper) and Class B (liquids & gases).

The Spray Foam unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough nylon valve assembly.

Minimum usable temperature is 4° F and the maximum usable temperature is 140° F.

Unit has passed 35 kv conductivity of discharge test.

At a Glance

- Model Foam
- AFFF Spray Foam
- UL Classified to BS EN3 1996
- EN3 rated 8A, 70B
- 5 year limited warranty
- Suitable for use on liquid & common combustibles

For use on the following types of fire:



Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 2 liters of fire extinguishing agent (Average)
- 5 year limited warranty
- Powder coated cylinder for corrosion protection
- Supplied with wall hanger



UPC: 0-47871-66620-1

Product Specification

Net agent weight (Average)	4.4 lb
Unit weight (Average)	7.5 lb
Diameter	4.5 inches
Height	16.07 inches
Discharge time	12-15 seconds
Discharge range	12-14 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Nylon
Strap Bracket	EN3 approved

Packaging Options



MASTER PACK