

# *Horizontal Lifeline*

---



Safety and mobility – these are the hallmarks of North’s Temporary Horizontal Lifeline (HLL) Systems. Whether rope or cable, these systems provide durable protection that can be moved from site to site where there are suitable approved anchor points. 100% portable and lightweight, these systems are ideal for the construction job site or bridge and building inspection activities.

## TEMPORARY HL KIT - ROPE

Made with synthetic kernmantle rope, this is the lightest of North’s horizontal lifelines. It spans up to 60 feet (18 m) for up to 2 people.



Part No	Description
<b>FP1001</b>	60’ (18 m) of 5/8” (16mm) synthetic lifeline rope, 2 carabiners, 2 anchor slings, 1 rope tensioner, 1 lanyard (4 foot) with energy absorber and convenient carrying bag.
<b>FP16ST/KH60</b>	60’ (18 m) horizontal lifeline, 5/8” (16 mm) hard lay polyester kernmantle rope, one termination and carabiner.
<b>FP85</b>	Carabiner connector, steel 1/4 turn twist lock, 5/8” (16 mm) opening.
<b>FP02/6</b>	PVC coated cable sling, 6’ (1,8 m) long.
<b>FP3521</b>	Rope tensioner for 5/8” (16 mm) kernmantle rope.
<b>FP22322/4</b>	25 mm (1”) nylon web lanyard with Soft Pack energy absorber, double locking ergonomic snap hook at both ends, 4 feet long.
<b>FP1010</b>	Large equipment carrying bag, ideal for lifeline kits.

## TEMPORARY HL KIT - CABLE

The “SteelMan” Temporary Horizontal Lifelines provide a durable version of the rope lifeline. Galvanized steel cable resists additional wear and tear found in severe environments. This kit is ideally used in construction, the petrochemical industry and steel erection. It spans up to 60’ (18 m) for up to 2 people.



Part No	Description
<b>FP1002</b>	Temporary HL Kit, comprising 60’ (18m) of 3/8” (10mm) galvanized cable, 2 anchor slings, cable tensioner and cable clips, Soft Pak energy absorber, 2 carabiner connectors.
<b>FP9380/60</b>	Galvanized cable 3/8” (10 mm), 60 feet long.
<b>FP03/6</b>	Pass through anchor sling 2” (50 mm) nylon webbing, one small and one large “D” ring, 6 feet long.
<b>FP9580</b>	Cable tensioner.
<b>FP9138</b>	Cable clip.
<b>FPD773</b>	Carabiner connector, steel, 1/4 turn twist lock, 3/4” (19 mm) opening.

## ACCESSORIES



Part No	Description
<b>FP3000</b>	CanRest metallic energy absorber for lifeline limits anchor loads to 2800 lbs (13kN)
<b>FP1800</b>	Replacement Soft Pak tear web energy absorber with weather proof cover. Reduces loads on end anchor to below 1800 lbs. (8 kN).
<b>FP1801</b>	Replacement Soft Pak tear web energy absorber. Reduces loads on end anchor to below 1800 lbs. (8 kN).
<b>FP9150</b>	Optional split pulley for use on horizontal lifelines.