Full Home Fire Extinguisher

Part number 21006704 Full Home use

POLL PIR, HOLD UNIT UPPEGHT.

STAND BACK I FEET AIM AT BASE

SQUEEZE LEVER SWEEP SADE TO

12

Meets NFPA recommendations for the home, garage and worksho

For use on the following

types of fire:

CKill

.

• . .

• . . •

. 6

e

6

.

.

6

e

6

đ •

•

.

•

6

.

0

¢ .

e ¢

.

0

. 6

e

e

6

0 .

• .

. • •

.

.

•

.

. .

.

• . e

• . • . • • • .

•

Single use

UL Rated 3-A, 40-B:C



The Full Home extinguisher offers exceptional fire fighting protection and value. The multipurpose unit meets NFPA requirements for living areas, as well as the garage and workshop.

The Full Home unit is the #1 choice for all round home protection and came top in a recent consumer survey.

Fights fires common to the home, garage and workshop such as textiles, paint, wood, gasoline & energized electrical equipment. This unit is easy to use and has a 10 year warranty.

Features bilingual nameplate and carton

At a Glance

- Model FX340GW
- . Multipurpose Dry Chemical
 - UL listed
- UL rated 3-A, 40-B:C •
- Supplied with wall hanger
- Monoammonium Phosphate
- 10 year limited warranty

Features

- Pressure gauge allows for • immediate pressure status check
- Easy-to-pull safety pin
- Rust and impact resistant nylon handle
- 5.5 lb. of fire extinguishing agent (Average)
- 10 year limited warranty
- UL approved wall hanger
 - Powder coated cylinder for corrosion protection





B · LIQUIDS

| Net agent weight (Average) | 5.5 lb. |
|----------------------------|-------------------|
| Unit weight (Average) | 8.25 lb. |
| Diameter | 4.5 inches |
| Height | 16.07 inches |
| Discharge time | 13-15 seconds |
| Discharge range | 12-18 feet |
| Operating pressure | 195 psi |
| Cylinder | Seamless aluminum |
| Valve, handle, lever | Nylon |
| Wall hanger | UL Listed |



Kidde Residential and Commercial Division

1016 Corporate Park Drive, Mebane, NC 27302 • Tel. 919.563.2711 • www.kidde.com