

ABC Fire Extinguishers

Easy-to-use and maintain. Specially fluidized and siliconized mono ammonium phosphate dry chemical. Insulates Class A fires and coats the surface to which it is applied. Smothers and breaks the chain reaction of Class B fires. Bar coded labels. Electrically non-conductive. Bracket included.



Cat#	Size	UL Rating	Valve	Application	Bracket	Price
P614	2 1/2 lbs.	1A:10B:C	Alum.	Nozzle	Wall/Vehicle	\$39.95
P615	5 lbs.	2A:10B:C	Alum.	Hose & Nozzle	Wall/Vehicle	\$58.95
AF557	5 lbs.	2A:10B:C	Brass	Hose & Nozzle	Wall	\$72.95
AF553	5 lbs.	3A:40B:C	Alum.	Hose & Nozzle	Wall/Vehicle	\$55.95
AF554	10 lbs.	4A:80B:C	Alum.	Hose & Nozzle	Wall	\$89.95
AF558	10 lbs.	4A:80B:C	Brass	Hose & Nozzle	Wall	\$103.95
AF555	20 lbs.	20A:120B:C	Alum.	Hose & Nozzle	Wall	\$150.95
J559	20 lbs.	20A:120B:C	Brass	Hose & Nozzle	Wall	\$172.95

Carbon Dioxide Extinguishers

Discharges a white cloud of "snow" which smothers a fire by eliminating its oxygen. Effective for Class B flammable liquid fires and is electrically non-conductive. Aluminum cylinder. Bracket included.



Cat#	Size	UL Rating	Valve	Application	Bracket	Price
H790	5 lbs.	5B:C	Brass	Horn	Wall	\$155.95
H791	10 lbs.	10B:C	Brass	Hose and Horn	Wall	\$236.95
H792	15 lbs.	10B:C	Brass	Hose and Horn	Wall	\$267.95
H793	20 lbs.	10B:C	Brass	Hose and Horn	Wall	\$331.95

Peerless Pump Type Water Extinguishers

Rated 2A, the Peerless Pump Type Water Extinguishers can be filled while in use and are simple-to-operate. You can test it without loss of water by directing the stream back into the tank. The operator controls the discharge. Moving parts made of corrosion-resistant brass and copper. Immediate operation; no priming needed.



2 1/2 Gallon Size

AF577	Polished Copper	\$401.95
R588	Chrome Plated Copper	\$392.95
R587	Red Enamel Copper	\$320.95
H897	Red Enamel Steel	\$285.95
R589	Vehicle Bracket	\$156.95

5 Gallon Size

AF578	Polished Copper	\$426.95
R591	Chrome Plated Copper	\$415.95
R590	Red Enamel Copper	\$371.95
H798	Red Enamel Steel	\$283.95
R592	Vehicle Bracket	\$156.95

Class D Fire Extinguishers

Safest unit on the market, with long hose and wand reach for operating safely. OSHA requires this type of extinguisher in manufacturing areas. **Sodium Chloride** based is specially designed to be used on burning metals, such as magnesium, sodium, potassium, sodium-potassium alloys, uranium and powdered aluminum. **Copper Agent** based is specially designed for use on lithium and lithium alloy fires. 30 lbs., hose & applicator. Wall bracket included.



AF559	Sodium Chloride	\$438.95
AF560	Copper Agent	\$720.95



Water & Foam Stored Pressure Extinguishers



Easy-to-use, maintain and service. Stainless steel cylinders, chrome-plated brass valve, and bar coded labels.

Water Extinguisher: utilizes the cooling, soaking and penetrating effect of 45-55 ft. stream of water for Class A fires. Optional loaded stream/anti-freeze charge protects from freezing.

Foam Extinguisher: uses FFFP foam for Class B fire fighting capability. Bracket included. Ship. wt. 9 lbs.

Options

AF579	Water Conditioner, 1 1/2 oz. bottle	\$5.95
BA180	Loaded Stream/Anti-Freeze Charge	\$56.95
AF581	FFFP Foam Refill	\$36.95

Cat#	Type	Size	UL Rating	Application	Bracket	Price
H795	Water	2 1/2 gal.	2A	Hose & Nozzle	Wall	\$111.95
				Hose & Air		
AF580	FFFP	2 1/2 gal.	3A:20B	Aspirating Nozzle	Wall	\$180.95

